

Leading Innovation, Creating Tomorrow

GLOFA GM Series



Automation Equipment



LS Industrial Systems
www.lsis.biz

Leader in Industrial Electric Power and Automation creating environment-friendly and highly productive industrial society as Total-solution provider

LS Industrial Systems (LSIS), founded in 1974, as a leader in Korean industrial electric power and automation market is trying to be a global leader. LSIS will fulfill its mission providing total-solution as a forerunner of creating environment-friendly and productive industrial future society.



Programmable Logic Controller



GLOFA GM Series

Programmable Logic Controller

Table of contents

GLOFA-GM7	9	Analog input module (GM4/6)	44
GLOFA-GM7U	11	Analog output module (GM4/6)	45
GLOFA-GM7/GM7U wiring diagram	14	Temperature control module (GM4)	46
GLOFA-GM7/GM7U expansion unit	16	Thermocouple module (GM4/6)	47
Block type PLC configuration	19	RTD module (GM4)	47
GLOFA-GM6	21	PID control module (GM4)	48
GLOFA-GM4	25	Analog timer module (GM4)	48
GLOFA-GM Fast Enet (Ethernet) system	32	Positioning module (APM): (GM4/6)	49
GLOFA-GM Ethernet system configuration	33	I/O interface with external equipment	50
GLOFA-GM Fnet (Fieldbus) system	34	Example of connection with drivers	52
GLOFA-GM Fnet system configuration	35	High speed counter module (GM4/6)	53
GLOFA-GM Cnet (Computer link) system	36	GLOFA-GM program S/W (GMWIN)	54
GLOFA-GM Cnet (Computer link) system configuration	37	PMU 30 series	55
GLOFA-GM Dnet (DeviceNet) system	38	XGT PANEL	56
GLOFA-GM Dnet system configuration	39	Command	57
GLOFA-GM Pnet (Profibus-DP) system	40	Product list	63
GLOFA-GM Pnet system configuration	41	Dimensions	67
SMART I/O	42	Cable connection	69
SMART I/O system configuration	43		



■ GLOFA-GM Series

Series	Specification				Network					
	Max. I/O points (Using remote I/O)	Execution speed (μs/step)	Memory capacity (byte)		Fast Enet	Fnet	Cnet	Dnet	Pnet	Rnet
			Program	Data						
GM4	GM4-CPUA 2,048 (4,096)	0.2	128K	52K	●	●	●	●	●	●
	GM4-CPUB 2,048 (8,192)	0.2	128K	50K	●	●	●	●	●	●
	GM4-CPUC 3,584 (32,768)	0.12	1M	428K	●	●	●	●	●	●
GM6	384	0.5	68K	32K	●	●	●	●	●	●
GM7	10~80	0.5	68K	32K	●	●	●	●	●	●
GM7U	20~120	0.1	132K	44K				slave	slave	

●Enet: Ethernet ●Fnet: Fieldbus ●Cnet: Computer Link ●Dnet: DeviceNet ●Pnet: Profibus-DP

●Rnet: Dedicated communication for LSIS SMART I/O


Series	Special modules							
	Analog I/O	High speed control	Position control	PID control	Thermocouple input	RTD	Analog timer	
GM4	7 Types G4F-AD3A (8Ch) G4F-AD2A (4Ch) G4F-DA3V (8Ch) G4F-DA2V (4Ch) G4F-DA3I (8Ch) G4F-DA2I (4Ch) G4F-DA1A (2Ch)	3 Types G4F-HSCA (1Ch) G4F-HO1A (2Ch) G4F-HD1A (2Ch) * 1)	6 Types G4F-PPXO * 1) G4F-PPXD (Axis X=1, 2, 3)	2 Types G4F-PIDB (16 loops) G4F-TMCA (2 loops)	1 Type G4F-TC2A (4Ch)	1 Type G4F-RD2A (4Ch)	1 Type G4F-AT3A (8 points)	
GM6	3 Types G6F-AD2A (4Ch) G6F-DA2V (4Ch) G6F-DA2I (4Ch)	4 Types G6F-HSCA (1Ch) G6F-HO1A (2Ch) G6F-HD1A (2Ch) * 1) Built-in (CPUC)	6 Types G6F-PPXO * 1) G6F-PPXD (Axis X=1, 2, 3)	Built-in (CPUB/CPUC)	1 Type G6F-TC2A (4Ch)			
GM7 * 2)		3 Types	Built-in (1Ch)					1 Type G7F-AT2A (4 points)
GM7U * 2)	7 Types	Built-in (4Ch)	Built-in Control axis: 2	Built-in		1 Type		

*1) -HO1A, -PPXO: Open collector type,

-HD1A, -PPXD: Line drive type

*2) Refer to P19

■ Part number name





IEC61131-3 Language



/ Open Network System



Powerful and compact PLC

CPU, digital I/O and power part are embedded in block-type PLCs, which is easy to install in whatever area you want for system configuration. In case of module-type PLCs, system configuration is easily achieved by a variety of modules (CPUs, I/O, special modules, network modules).

® Number: E124950



GM7/GM7U

Global standard (IEC61131-3) language

- IL (Instruction list)
- LD (Ladder diagram)
- SFC (Sequential function chart)

Dedicated CPU (one-chip) for high speed processing time

- GM4 ($0.2\mu s$ /step)
- GM4C ($0.12\mu s$ /step)
- GM6 ($0.5\mu s$ /step)
- GM7 ($0.5\mu s$ /step)
- GM7U ($0.1\mu s$ /step)

Convenient programming tool

- Windows 95/98/ME/NT/2000/XP based
- Editing, Monitoring, Debugging function by symbol
- Supports IL, LD, SFC language
- Simulation without PLC

GLOFA GM

Programmable
Logic ...
Controller
Serie

LS GLOFA
GM Series

GM4

GM6

GM7



GM6



GM4

International standard communication protocol suitable for CIM.

Various special function module

International standard Ethernet (GM4/6)

- Enet Modules (Ethernet, 10/100Mbps)
- Fnet Modules (Fieldbus, 1Mbps)
- Dnet Modules
(DeviceNet, 125k, 250k, 500kbps)
- Pnet Modules
(Profibus-DP, 9.6kbps~12Mbps)

- Analog I/O modules
- High speed counter modules
- Position control modules
- RTD, Thermocouple Input modules
- PID, Analog timer module

- Fast Ethernet (10/100Mbps)
- 100BASE-T, 10BASE-5, support
- IEEE802.3 & Protocol
(TCP/IP, UDP/IP)
- Communication with other
PLC Systems using function block (FB)
- Two types: open Ethernet,
dedicated Ethernet

■ General specifications

Item	Description			Standard
Ambient temperature	0~55°C (32~131°F)			
Storage temperature	-25~70°C (-13~158°F)			
Ambient humidity	5~95%RH (Non-condensing)			
Storage humidity	5~95%RH (Non-condensing)			
Vibration	Occasional vibration			
	Frequency 10 ≤ f < 57 Hz	Acceleration -	Pulse width 0.075mm	
	57 ≤ f ≤ 150 Hz	9.8% (1G)	-	
	Continuous vibration			
	Frequency 10 ≤ f < 57 Hz	Acceleration -	Pulse width 0.035mm	
	57 ≤ f < 150 Hz	4.9% (0.5G)	-	
Shocks	<ul style="list-style-type: none"> Peak acceleration: 147% (15G) Duration: 11ms Half-sine, 3 times each direction per each axis 			
	Square wave impulse noise Electrostatic discharge Radiated electromagnetic field noise			LSIS Standard IEC 61131-2/IEC 1000-4-2 IEC 61131-2/IEC 1000-4-3
Impulse noise	Fast transient/ burst noise	Power supply 2kV	Digital I/O (more than 24V) 1kV	Digital I/O (>24V) Analog I/O, Comm.I/O 0.25kV
	Operation ambience			Free from corrosive gases and excessive dust
Altitude	Up to 2,000m (6,562ft)			
Pollution degree	Less than or equal to 2*			
Cooling method	Air-cooling			

* Pollution degree 2 is nonconductive pollution of the sort where occasionally a temporary conductivity caused by condensation must be expected.

■ Technical specifications

Item	GM4-CPUA/B	GM4-CPUC	GM6	GM7	GM7U
Control method	Cyclic execution of stored program, Interrupt task execution				
I/O Updating method	Program refresh per 1 scan				
Program languages	IL (Instruction list) / LD (Ladder diagram) / SFC (Sequential function chart)				
Number of Instructions	Operator				
	Standard function	194	194 + 'real number F'	194	
Configuration speed	Special function block	Special function blocks for special modules			
	Operator	0.2μs/step	0.12μs/step	0.5μs/step	0.1μs/step
I/O points	Standard function/ Standard function block	0.2μs/step	0.12μs/step	0.5μs/step	
	Using 32pt module	1,024	1,792	384	10~80
	Using 64pt module	2,048	3,584	-	-
	Network	4,096 / 8,192	32,768	-	-
Program capacity	128K *	1M	68K	132K	
I/O points	Direct variable area	2~16K	8~117K	2~8K	10K
	Symbolic variable area *	52K/50K	428K	32K	30K
Timer *	Not limited, Time range: 0.001~4294967.295 sec (1,193hours)				
Counter *	Not limited, Count range: -32,768~32,767				
Operation mode	RUN, STOP, PAUSE, DEBUG				
Data retention at power failure	Set "retain" at data declaration				
Program type	Scan	180			
	Time driven	8	32		
					8
	External				8
					8
	Internal				4
HSC					
Error	-	_ERR_SYS			
Initialization				_INIT	
Self-diagnosis	Execution, Delay, Memory error, I/O error, Battery error, Power supply error				
Restart mode	Cold, Warm, Hot restart			Cold, Warm restart	

* K: kilobyte

* One timer occupies 20 bytes in symbolic variable area

* Symbolic variable area: Maximum symbolic area - Direct variable area

* One counter occupies 8 bytes in symbolic variable area

Number of communication module installation



GLOFA GM Series
Programmable Logic Controller

■ GM4/6

Item	GM4-CPUA	GM4-CPUB	GM4-CPUC	GM6-CPUA/B/C
No. of total communication modules	4	4	8	4
Cnet only	4	4	8	4
High-speed link modules	2	4	8	2
Cnet + HSL link modules	2 + 2	2 + 2	8 in total	2 + 2

Item	Cnet I/F module	HSL module	Installation in expansion base
GM4-CPUA	4	2	×
GM4-CPUB	4	4	○
GM4-CPUC	8	8	○

Network support in GM4/6

- Master (High-speed link): Fnet, Rnet, DeviceNet, Fast Ethernet, Profibus-DP
- Cnet: RS-232C, RS-422/485
- MODBUS (ASCII/RTU) as slave inserting MODBUS library into Cnet module

■ GM7/GM7U

Item	GM7U	GM7 (10 point)	GM7 (20 to 60 point)
No. of total communication modules	2 (built-in Cnet included)	1	1
Cnet only	2 Built-in RS-485 is included.	1 Built-in RS-232C/485 Simultaneous use is not allowed.	1 Built-in RS-232C or Cnet I/F module. Simultaneous use is not allowed.
High-speed link modules	1	Option unit is not allowed	Only 1
Cnet + HS link modules	1 + 1 (built-in RS-485 + HSL 1)		

Network support in GM7/GM7U

- Master (High-speed link): Fnet^{*1}, Rnet^{*2}
- Slave (High-speed link): Profibus-DP^{*3}, DeviceNet^{*3}
- Cnet: RS-232C, RS-422/485
- MODBUS (ASCII/RTU) as master/slave in parameter setting (GMWIN)

*1) LS dedicated protocol for Fnet I/F modules

*2) LS dedicated protocol for SMART I/Os

*3) Slave only



GLOFA-GM7

Programmable Logic Controller

■ Features

- High function and high performance with dedicated MPU chip
 - IEC 61131-3
- GLOFA-GM Network
 - Fnet, Rnet as master module
 - DeviceNet, Profibus-DP as slave module
- Various built-in functions
 - High speed counter 1 point (1-phase 16kHz, 2-phase 8kHz)
 - Pulse output 1 point (2kHz only available in Tr-output module)
 - PID loop with autotuning
 - Pulse catch 8 points (pulse catch: Min. 0.2ms)
 - Input filter (Noise reduction)
- External interrupt point: 8 points
(Task program execution by external interrupt input)
- RS-232C interface 1 channel (Built-in Cnet):
dedicated, User-defined, Modbus protocol



■ Specifications

Item		Specifications		Remark	
Operation method		Cyclic execution of stored program, Time-driven operation, Internal task operation			
I/O control method		Scan synchronized batch processing method (Refresh method)		Immediate input/output is available by 'Direct I/O' function	
Program language		IL (Instruction list) / LD (ladder diagram) / SFC (Sequential function chart)			
Number of Instructions	Operator	LD: 13, IL: 20			
	Standard function	194			
	Standard function block	12			
	Special function block	Each special module has its own special function block			
Processing speed	Operator	0.5 μ s / instruction			
	Standard function/function block	0.5 μ s / step			
Programming memory capacity		68K		Built-in flash memory (128K)	
I/O points		From 10 to 80 points (according to modules)			
Data Memory	Direct variable area (DVA)	2~8K		Setting in GMWIN	
	Symbolic variable area (SVA)	32K - Direct variable area			
Timer		No limitation. Time range: 0.001~4294967.295 sec (1193 hours)		20 bytes per 1 timer in SVA	
Counter		No limitation. Count range: -32768~32767		8 bytes per 1 counter in SVA	
Operation mode		RUN, STOP, PAUSE, DEBUG			
Data retention at power failure		Set to 'Retain' at data declaration			
Number of program blocks		100			
Program type	Task	Scan	100 - (Number of program blocks in task)		
		Time-driven	8		
		External	8		
		Internal	8		
		Initialization	1 (_INIT)		
Self-diagnostic function		Watchdog timer, Memory error, I/O error, etc			
Restart mode		Cold, Warm			
Built-in function	PID control	Control by function block, Autotuning, Forward/Reverse operation, Manual output, Operation scan time setting			
		Dedicated, Modbus, User-defined protocol			
	HSC	Counting speed	1-phase 16kHz, 2-phase 8kHz		
		Counting method	1-phase up/down counter (up/down: selection by program) 1-phase up/down counter (up/down: selection by B-phase) 2-phase up/down counter (up/down: Automatic selection by phase difference)		
		Multiplication	1, 2 or 4		
		Task program running	Task program running when the current value of HSC reaches the setting value		
		Pulse catch	Min. pulse width: 2ms, Maximum 8 points available to use		
		Pulse output	2kHz, 1Ch		
		External interrupt Input	8 points		
		Input filter function	0~15ms (Setting by 1ms)		

* 1) Built-in RS-232C signal: 4 (Rx), 7 (Tx), 5 (SG)

* G7M-DR10A, G7M-DR10A (/DC), G7M-DT10A: RS-232C and RS-485 port are embedded.
(Simultaneous use is not allowed) and a communication option module is not available.

GLOFA-GM7

Programmable Logic Controller

Input/output specifications

■ Input part

Item	Type	Main					Expansion
		G7M-DR10A (/DC) G7M-DT10A	G7M-DR20A(/DC) G7M-DT20A	G7M-DR30A (/DC) G7M-DT30A	G7M-DR40A (/DC) G7M-DT40A	G7M-DR60A (/DC) G7M-DT60A	
Power supply for main module		G7M-DR□□A, G7M-DT□□A: AC100~240V (50/60Hz), G7M-DR□□A/DC: DC24V					
Input point	6	12	18	24	36	6	
Insulation method		Photocoupler					
Rated input voltage		DC24V					
Rated input current		7mA (%Ix0.0~%Ix0.2: 16mA)					
Operation voltage range		DC20.4V~28.8V (Ripple rate < 5%)					
Max. simultaneous input		100% Simultaneous ON					
On voltage/current		DC19V or higher/5.7mA or higher (%Ix0.0~%Ix0.2: 12.7mA or higher)					
Off voltage/current		DC6V or lower/1.8mA or lower (%Ix0.0~%Ix0.2: 4mA or lower)					
Input impedance		3.3kΩ					
Response time	Off → On	15ms or less*					
	On → Off	15ms or less*					
Operating indicator		LED					

* It is available to set from 1ms to 15ms in parameter of GMWIN (unit: ms)

■ Relay output part

Item	Type	Main					Expansion
		G7M-DR10A (/DC)	G7M-DR20A (/DC)	G7M-DR30A (/DC)	G7M-DR40A (/DC)	G7M-DR60A (/DC)	
Output point		4	8	12	16	24	4
Insulation method		Relay insulation					
Rated load voltage/current		DC24V/2A (Resistive load), AC220V/2A (COS φ =1)/point, 5A/COM					
Min. load voltage/current		DC5V/1mA					
Max. load voltage		AC250V, DC110V					
Off leakage current		0.1mA or less (AC220V, 60Hz)					
Max. on/off frequency		1,200 times/hr					
Surge absorber		-					
Service life	Mechanical	20million times or more					
	Electrical	100,000 times or more (Rated voltage/current load) AC200V/1.5A, AC240V/1A (COS φ =0.7) 100,000 times or more AC200V/1A, AC240V/0.5A (COS φ =0.35) 100,000 times or more DC24V/1A, DC100V/0.1A (L/R=7ms) 100,000 times or more					
Response time	Off → On	10ms or less					
	On→ Off	12ms or less					
Operating indicator		LED					

■ Transistor output part

Item	Type	Main					
		G7M-DT10A	G7M-DT20A	G7M-DT30A	G7M-DT40A	G7M-DT60A	
Output point		4	8	12	16	24	
Insulation method		Photocoupler					
Rated load voltage		DC12/24V					
Operating load voltage		DC10.2~26.4V					
Rated load current		0.5A/point, 3A/COM					
Off leakage current		0.1mA or less					
On voltage drop		1.5V or less (Max.load)					
Surge absorber		Clamp diode					
Common	4 points/COM Sink type	8 points/COM Sink type	8 points/COM 4 points/COM Sink type	8 points/COM (×2) Sink type	8 points/COM (×3) Sink type		
Response time	Off → On	2ms or less					
	On→ Off	2ms or less					
Operating indicator		LED					



GLOFA-GM7U

Programmable Logic Controller



■ Features

Powerful built-in functions

- High-speed counter: 32-bit signed operation,
 - Counter range: -2,147,483,648 ~ 2,147,483,647
 - Function: ring counter, latch counter, comparison (equal /zone/task), RPM
- Positioning function (DRT/DT type)
 - Control axis: 2 axes (100kHz)
 - Operation method: single, repeat
 - Operation mode: end, keep, continuous
 - Additional functions: return to origin, JOG operation, PWM output
- PID operation function
 - Relay/PRC auto-tuning, SV ramp, delta MV, PWM output, position/velocity algorithm, Forward/Reverse

Various expansion modules

- 7 Digital I/O modules: G7E-DR(08/10/20)A, G7E-TR10A, G7E-DC08A, G7E-RY(08/16)A
- 9 Analog I/O modules: G7F-ADHA(B/C), G7F-AD2A(B), G7F-DA2(V), G7F-AT2A, G7F-RD2A
- 6 Comm. modules: G7L-CUEB(C), G7L-DBEA, G7L-PBEA, G7L-FUEA, G7L-RUEA
- 2 Option modules: G7E-RTCA, G7M-M256B

■ Specifications

Item		20	30	Specifications	40	60	Remark
Output type				DR type: Relay output DRT type: NPN Tr output + Relay output DT (N) type: NPN Tr output DT (P) type: PNP Tr output			
Operation method				Cyclic execution of stored program, Time-driven operation, Internal task operation			
I/O control method				Scan synchronized batch processing method (Refresh method)			
Program language				IL (Instruction list) / LD (ladder diagram) / SFC (Sequential function chart)			
Number of Instructions	Operator			LD: 13, IL: 20			
	Standard function			194			
	Standard function block			12			
	Special function block			Function blocks for built-in functions, special, communication modules			
Processing speed for operator				0.1~0.9 μ s/step			
Program memory capacity				132 Kbyte (including parameters)			
I/O points				Input: 12, Output: 8 Input: 18, Output: 12 Input: 24, Output: 16 Input: 36, Output: 24			Max. 120
Data Memory	Direct variable area (DVA)			14K			
	Symbolic variable area (SVA)			30K			
Timer				No limitation. Time range: 0.001~4294967.295 sec (1193 hours)			
Counter				No limitation. Count range: -32768~32767			
Operation mode				RUN, STOP, PAUSE, DEBUG			
Data retention at power failure				Set to 'Retain' at data declaration			
Number of program blocks				100			
Program type	Scan			100 - (Number of program blocks in task)			
	Time-driven			8			
	External			8			
	Task	Internal		8			8 in total
		HSC		4			
		Initialization		1 (_INIT)			
Self-diagnostic function				Watchdog timer, Memory error, I/O error, etc			
Restart mode				Cold, Warm			
Built-in function	PID control			Control by function block, Autotuning, Forward/Reverse operation, Manual output, Delta MV, SV ramp function, Anti-windup, etc			
	Cnet interface			Dedicated, LS Inverter, MODBUS, User-defined, No protocol			
	HSC	Counting speed		1-phase: 100kHz (2channels) / 20kHz (2channels) 2-phase: 50kHz (1channel) / 10kHz (1channel)			
		Counting method		1-phase up counter 1-phase up/down counter (up/down: selection by B-phase) 2-phase up/down counter (up/down: pulse input) 2-phase up/down counter (up/down: automatic selection by phase difference)			
		Additional		Internal/external preset, Latch counter, Comparison output, RPM			
		Basic		No. of control axis: 2, Control method: PTP/speed/synchronous, Control unit: pulse Positioning data: 20/axis (operation step no. 1~20)			
	Position	Positioning		Position method: absolute/incremental, Operation method: single/repeat Address range: -2,147,483,648~2,147,483,647 Speed: Max. 100kpps (setting range: 5~100,000pps) Acceleration/Deceleration method: Trapezoidal method			DRT/DT type only
		Return to origin		DOG/HOME (ON), DOG/HOME (OFF), approximate origin			
		JOG		Setting range: 5~100,000 (high/low speed)			
		Pulse catch		Minimum pulse width: 10 μ s (2 points), 50 μ s (2 points)			
		External interrupt		10 μ s (2 points), 50 μ s (2 points)			
		Input filter		0, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000ms (Default: 10ms)			

GLOFA-GM7U

Programmable Logic Controller

Input/output specifications

■ Input part

Item	Type	Main			
		G7M-DR20U (/DC)	G7M-DR30U (/DC)	G7M-DR40U (/DC)	G7M-DR60U (/DC)
	G7M-DT20U (N) (/DC)				
	G7M-DT20U (P) (/DC)				
	G7M-DRT20U (/DC)				
Power supply		G7M-DR□□U, G7M-DT□□U, G7M-DRT□□U; AC100~240V (50/60Hz), G7M-DR□□U/DC, G7M-DT□□U/DC, G7M-DRT□□U/DC: DC12/24V			
Input point		12	18	24	36
Insulation method		Photocoupler			
Rated input voltage		DC24V			
Rated input current		7mA (%Ix0.0~%Ix0.3 [9mA])			
Operating voltage range		DC20.4V~28.8V (Ripple rate <5%)			
Max. simultaneous input		100% simultaneous ON			
On voltage/current		DC19V or higher/5.7mA or higher			
Off voltage/current		DC6V or lower/1.8mA or lower			
Input impedance		About 3.3 kΩ (%Ix0.0~%Ix0.3 [2.7 kΩ])			
Response time	Off → On On → Off	0, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000ms (Default: 10ms) 0, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000ms (Default: 10ms)			
Operating indicator		LED			

■ Relay output part

Item	Type	Main			
		G7M-DR20U (/DC)	G7M-DR30U (/DC)	G7M-DR40U (/DC)	G7M-DR60U (/DC)
Output point		8	12	16	24
Insulation method		Relay insulation			
Rated load voltage/current		DC24V/2A (Resistive load), AC220V/2A (COS φ=1)/point, 5A/COM			
Min. load voltage/current		DC5V/1mA			
Max. load voltage		AC250V, DC110V			
Off leakage current		0.1mA or less (AC220V, 60Hz)			
Max. on/off frequency		1200 times/hr			
Surge absorber		None			
Service life	Mechanical Electrical	20 million times or more 100,000 times or more (rated load voltage)			
Response time	Off → On On → Off	10ms or less 12ms or less			
Operating indicator		LED			

■ Transistor/mixed output part

Item	Type	Main			
		G7M-DT20U (N)* ¹ (/DC)	G7M-DT30U (N) (/DC)	G7M-DT40U (N) (/DC)	G7M-DT60U (N) (/DC)
		G7M-DT20U (P)* ² (/DC)	G7M-DT30U (P) (/DC)	G7M-DT40U (P) (/DC)	G7M-DT60U (P) (/DC)
Output point	DT-type output point	8	12	16	24
	DRT-type Tr. output point	4	4	4	4
	DRT-type relay output point	4	8	12	20
Insulation method		Photocoupler (Tr. output points), Relay insulation (Relay output points)			
Rated load voltage		DC12V/24V			
Operation load voltage		DC10.2~26.4V			
Max. load voltage		0.5A/point (DRT type: %Qx0.0~%Qx0.3 (0.1A/point), DT type: %Qx0.0~%Qx0.1 (0.1A/point))			
Off leakage current		0.1mA or less			
Voltage drop		Less than DC0.3V			
Surge absorber		Zener diode			
Inrush current		Less than 4A, 10ms			
Response time	Off → On On → Off	0.2ms or less (Tr) 0.2ms or less (Tr)			
Operating indicator		LED			

*1) (N) stands for NPN Tr.

*2) (P) stands for PNP Tr.

* For the characteristics of relay outputs in a DRT-type module, please refer to the output part (relay) in the above.

Expansion specifications

■ Input part

Item	Type	Expansion			
		G7E-DC08A *	G7E-DR08A *	G7E-DR10A	G7E-DR20A
Input point		8	4	6	12
Insulation method			Photocoupler		
Rated input voltage				DC24V	
Rated input current				7mA	
Operating voltage range				DC20.4V~28.8V (Ripple rate <5%)	
Max. simultaneous input				100% simultaneous ON	
On voltage/current				DC19V or higher/5.7mA or higher	
Off voltage/current				DC6V or lower/1.8mA or lower	
Input impedance				About 3.3 kΩ	
Response time	Off → On			0, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000ms (Default: 10ms)	
	On → Off			0, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000ms (Default: 10ms)	
Operating indicator				LED	

■ Relay output part

Item	Type	Expansion				
		G7E-RY08A *	G7E-RY16A	G7E-DR08A *	G7E-DR10A	G7E-DR20A
Output point		8	16	4	4	8
Insulation method				Relay insulation		
Rated load voltage/current				DC24V/2A (Resistive load), AC220V/2A (COS φ =1)/point, 5A/COM		
Min. load voltage/current				DC5V/1mA		
Max. load voltage				AC250V, DC110V		
Off leakage current				0.1mA or less (AC220V, 60Hz)		
Max. on/off frequency				1200 times/hr		
Surge absorber				None		
Service life	Mechanical			20 million times or more		
	Electrical			100,000 times or more (rated load voltage)		
Response time	Off → On			10ms or less		
	On → Off			12ms or less		
Operating indicator				LED		

■ Transistor output

Item	Type	Expansion	
		G7E-TR10A	
Output point		10	
Insulation method		Photocoupler	
Rated load voltage		DC12/24V	
Operation load voltage		DC10.2~26.4V	
Max. load voltage		0.5A/points, 4A/COM	
Off leakage current		0.1mA or less	
Inrush current		Less than 4A, 10ms	
Voltage drop		Less than DC1.5V	
Surge absorber		Clamp diode	
Response time	Off → On	2ms or lower	
	On → Off	2ms or lower	
Operating indicator		LED	












* Slim type

GLOFA-GM7/GM7U wiring diagram

Programmable Logic Controller

Wiring diagram

■ Input/Output (Relay output) & Input/Output (Expansion)

G7M-DR10A (/DC)	G7M-DR20A (/DC) / G7M-DR20U (/DC)	G7M-DR30A (/DC) / G7M-DR30U (/DC)		
				
G7M-DR40A (/DC) / G7M-DR40U (/DC)	G7M-DR60A (/DC) / G7M-DR60U (/DC)	G7E-DR08A *1)		
				
G7E-DR10A	G7E-DR20A *1)	G7E-DC08A *1)	G7E-RY08A *1)	G7E-RY16A *1)
				

*1) GM7U only

* All the /DC types need DC24V for their operation and they don't supply DC24V output.

*  stands for GM7 series


* Refer to user's manual for wiring.

■ GM7 DT Output



■ GM7U DT/DRT output

■ Output expansion unit



* Input terminal of transistor output modules is identical to that of relay output.

You should connect DC24V to P terminal when you use an external power supply for load operation.

* Refer to user's manual for wiring.

GLOFA-GM7/GM7U expansion unit

Programmable Logic Controller

Analog input/output unit

Item		A/D • D/A Hybrid module G7F-ADHA (C) *1		A/D Module G7F-AD2A (B) *2		D/A Module G7F-DA2I		G7F-DA2V						
Analog input	Input range	Voltage	DC 0~10V (Input resistance: More than 1 MΩ)				Set by jumper pin for V/I selection upper part of product (Up: V, down: I)							
		Current	DC 0~20mA (Input resistance 250 Ω) DC 4~20mA (Input resistance 250 Ω)											
	Digital output		Classified by parameter 12 bits (0~4,000)				Set by dip S/W for V/I selection on left side of product (Left: V, right: I)							
	Voltage/current selection		V/I selected by GMWIN parameter Short V and I terminal when current input is used.											
	No. of channel		2Ch/module		4Ch/module		Set by input terminal (When current input is used, short the V and I terminal)							
	Absolute max. Input	V	DC+12V		DC±15V									
		I	DC+24mA		DC±25mA									
Analog output	Output range	V	DC 0~10V (External load resistance 2 kΩ ~ 1 MΩ)				DC 0~20mA (Load resistance 510 Ω) DC 4~20mA (Load resistance 510 Ω)							
		I	DC 0~20mA (External load resistance 510 Ω) DC 4~20mA (External load resistance 510 Ω)											
	Classified by parameter								DC 0~10mA (Load resistance 2 kΩ ~ 1 MΩ)					
	Digital input		12 bits (0~4,000)				12 bits (0~4,000)							
	Voltage/current selection		Separated from terminal											
	No. of channel		1Ch/module	2Ch/module		4Ch/module								
	Absolute V max. output	V	DC +12V		DC +24mA									
		I	DC +24mA		DC +12V		DC 0~20mA: 5μA (1/4000) DC 4~20mA: 6.25μA (1/3200)							
Common	Max. resolution	V	DC 0~10V: 2.5mV (1/4000)				2.5mV (1/4000)							
		I	DC 0~20mA: 5μA (1/4000)											
	Accuracy		DC 4~20mA: 6.25μA (1/3200)				0.5%							
	Max. conversion speed		±0.5% (Full scale)											
	Insulation		1 ms/Ch + scan time (GM7U), 2ms/Ch + scan time (GM7)500 μs *3 + scan time				1 ms *3 + scan time							
	Photocoupler insulation between I/O terminal and PLC power supply (Non-insulation between channels).													
	Connect terminal		9 points 2 terminals	8 points 2 terminals		2 points/16 points terminals	16 points terminal		8 points 2 terminals					
	Internal current consumption		20mA	20mA		100mA	20mA		15mA					
	External power supply	V	DC 21.6~26.4V				80mA							
		I	80mA	95mA		100mA	90mA							
Weight		240g		180g		300g	280g		160g					

* Caution for wiring • 2-core, shielded twisted pair cable is recommended. Size: AWG22 (0.3mm²) or higher.

• Wiring with high voltage or generation line, it makes induction failure which may cause malfunction or be out of order.

*1) Input voltage range of G7F-ADHC is DC 0~1V and the rest features are equal to those of G7F-ADHA. This is available at GM7U

GM7 only: G7F-ADHA, G7F-AD2A (B)

*2) G7F-AD2B is a slim type

*3) 500 μs G7F-DA2I is for all channels. So it is 1ms in G7F-DA2V.

* Slim type: G7F-ADHB, G7F-AD2B, G7F-DA2V, G7F-RD2A

G7F-RD2A

Item		Specifications	
Connectable RTD		• Pt100 (JIS C1640-1989, DIN 43760-1980)	• JPt100 (KS C1603-1991, JIS C1604-1981)
Temperature input range		• Pt100: -200~600°C (18.48 to 313.59Ω)	• JPt100: -200~600°C (17.14 to 317.28Ω)
Digital output		• Digital conversion value: 0~4,000	• Detected temperature value: -2000~6000 (10-time scaled up value)
Burnout detection		Each of three wires at every channel has detection function	
Accuracy		±0.5% (Full scale)	
Maximum conversion speed		40scan/module	
Number of temperature input device points		4 channels/module	
Insulation method		Photocoupler insulation between the input terminal and PLC power supply (Non-insulation between channels)	
Connection terminal block		Two 8-point terminal blocks	
Internal current consumption		25mA	
External power supply	V	DC 21.6~26.4V	
	I	70mA	
Weight		240g	

G7F-AT2A

Item	Specification
Channels	4
Output value range	8 bits (0 ~ 200)
Setting type	Setting by variable resistance
Accuracy of timer	±2.0% (Accuracy about max. value)
Internal current consumption	50mA
Weight	200g

Communication unit

Cnet modules

(G7L-CUEB, G7L-CUEC)



Item		Specifications
Interface		G7L-CUEB: RS-232C (Modem), G7L-CUEC: RS-422/485
Communication mode	Dedicated mode	Supports 1:1, 1:N and high-speed link
	GMWIN mode	Supports remote programming and mounting via GMWIN
	Modbus mode	Supports master and slave function with Modbus protocol (ASCII, RTU)
	User-defined mode	Supports user-defined communication
Data structure	Data bit	7 or 8
	Stop bit	1 or 2
	Start bit	1 or 2
	Parity bit	EVEN/ODD/NONE
Synchronization		Asynchronous method
Transmission speed		1,200 / 2,400 / 4,800 / 9,600 / 19,200 / 38,400 / 57,600bps
Setting method		Communication parameter setting in GMWIN
Distance		Max. 15m (CUEB), Max. 500m (CUEC)
Max. number of stations		Max. 32 stations
Weight		180g

Fnet/Rnet module (G7L-FUEA/RUEA) *1



Item		Specifications
Transmission speed		1Mbps
Communication	Segment	Max. 750m
	Repeater (Up to 6)	Max. 5.25km
Max. number of stations		Max. 64 stations
Setting method		Communication parameter setting in GMWIN
Cable		Shielded twisted pair cable
Weight		220g

*1) Rnet is a dedicated protocol for LSIS SMART I/Os.

Pnet module (G7L-PBEA)



Item		Specifications
Network type		Profibus-DP (Slave)
Protocol		EN50170/DIN19245
Media access Token passing & Poll		
Transmission and speed	Network	1200m (9.6~187kbps) / 400m (500kbps) / 200m (1.5Mbps) / 100m (3~12Mbps)
	Segment	127 stations
Max. Node		32 stations
Interface		RS-485 (electric)
Setting method		Communication parameter setting in GMWIN
Cable		Shielded twisted pair cable
Weight		210g

Dnet module (G7L-DBEA)



Item		Specifications			
Network structure		Trunk/drop line			
Protocol		Peer explicit message, Predefined explicit message Predefined I/O message (Poll, bit strobe, COS, cyclic)			
Max. extension & speed	Speed	500kbps	Network distance	100m or less	Drop cable
		250kbps	250m or less	6m or less	39m or less
		125kbps	500m or less	6m or less	78m or less
Channel		64 stations			
Diagnosis function		CRC error check/Scan list			
Setting method		Communication parameter setting in GMWIN			
Cable		5 lines (signal 2 lines, power 2 lines, shield 1 line)			


* 1) In case of GM7, only 1 communication module is available and you are not able to use a communication module and built-in Cnet at the same time because they are set as CH0 in GMWIN parameter. You are not able to connect a communication module to G7M-DR10A (DC) and G7M-DT10A, which support either RS-232C or RS-485, and you can select a communication channel using a dip switch (built-in). If it is on, RS-232C is enabled and if it is off, RS-485 is activated.

* 2) In case of GM7U, only 1 communication module is available and you are not able to use a communication module and built-in RS-232C at the same time because they are set as CH0 in GMWIN parameter. Besides you are able to use both CH0 and built-in RS-485 (CH1) simultaneously. For more information, refer to P8 and P18.


GLOFA-GM7/GM7U expansion unit

Programmable Logic Controller

■ GM7U type



[Built- in Cnet dip S/W: ON]



[Built- in Cnet dip S/W: OFF]

When built-in dip S/W is on, you are not supposed to use an expansion communication module while the built-in Cnet port is enabled, and if it's off, you can use an expansion communication module but the built-in Cnet port is disabled.

■ GM7 type




[Built- in Cnet dip S/W: ON]



[Built- in Cnet dip S/W: OFF]

1. Only one channel (Ch0) for communication except the loader port is available in economic types.
2. When the built-in dip S/W is on, you are not supposed to use an expansion Cnet module while the built-in Cnet port is enabled, and if it's off, you can use an expansion communication module but the built-in Cnet port is disabled.

■ GM7 10-point type: G7M-DR10A (/DC), G7M-DT10A



[Built- in Cnet dip S/W: ON]

1. If the built-in Cnet dip S/W is on, you are able to use RS-232C (4, 7, 5 pins) as Ch0 and if it is off, RS-485 is enabled as Ch0.
2. With these modules you are not supposed to connect a modem to RS-232C for download/upload, monitoring or controlling. To use a dedicated/dial-up modem, you are required to use G7L-CUEB as expansion comm. module and before applying a modem, please contact LSIS.
3. You are able to use an expansion Cnet module when you do not use built-in Cnet (RS-232C/485) after turning off the built-in Cnet dip switch. In this case, no other device is connected to the built-in RS-485 port.

Block type PLC configuration

Programmable Logic Controller

■ System configuration for GM7


Item	System configuration
GM7	<ul style="list-style-type: none"> Available system (max. 3 units in total) Digital I/O: max. 2 units Analog I/O: max. 2 units Analog timer: max. 3 units Communication I/F: 1 unit

■ System configuration



* I/O assignment applies to digital expansion module. For example, if an analog module is used at the 1st expansion and digital I/O is used at the 2nd expansion, then, the input of 2nd expansion module is from %Ix0.2.0 and the output is from %Qx0.2.0 And I/O assignment of GM7 and GM7U is equal

■ System configuration (GM7)



Option Pack

- Base unit used: Connect to the expansion connector of the basic unit.
- Expansion unit connected: Connect to the expansion connector of the last connected one.
- You are able to use only one option pack.

*1) When digital I/Os are used, the 1st expansion input is assigned from %Ix0.0.0 and its output from %Qx0.0.0. The 2nd expansion input is from %Ix0.1.0 and its output from %Qx0.1.0 and so on. I/O allocation does not apply to other expansion modules. It does only to digital expansion modules.

*2) You are not able to connect a communication module to G7M-DR10A/DC) and G7M-DT10A while you can do a communication module to other types of GM7. Built-in Cnet and a communication module share the same communication port and you are not able to use them at the same time.

*3) Option pack is not included.

Block type PLC configuration

Programmable Logic Controller

■ System configuration for GM7U

Base unit

- Processing speed: $0.1\ \mu s$
- Program capacity: 132k
- 32 types:
 - G7M-DR/DRT/DT20U (N/P) *1 (/DC)
 - G7M-DR/DRT/DT30U (N/P) (/DC)
 - G7M-DR/DRT/DT40U (N/P) (/DC)
 - G7M-DR/DRT/DT60U (N/P) (/DC)


*1) (N): NPN Tr., (P): PNP Tr.

Max. number of expansion unit installation

- Max. 3 units in total

Installation	Max. number of installation
Digital I/O	3
Analog I/O	3
Analog timer	3
Communication I/F	1

- You are able to connect an option pack to the connector of the last expansion module



■ Expansion modules *1)

Digital I/O modules

- Input
 - G7E-DC08A *2): DC input 8 points
- Output
 - G7E-TR10A *2): Tr output 10 points
 - G7E-RY08A *2): Relay output 8 points
 - G7E-RY16A *2): Relay output 16 points
- Input/Output
 - G7E-DR08A *2): DC in 4 points / relay out 4 points
 - G7E-DR10A: DC in 6 points / relay out 4 points
 - G7E-DR20A *2): DC in 12 points / relay out 8 points

Special modules

- A/D
 - G7F-AD2A, G7F-AD2B : Analog input (4 channels)
- D/A
 - G7F-DA2V *2): Voltage output (4 channels)
 - G7F-DA2I *2): Current output (4 channels)
- A/D, D/A
 - G7F-ADHA: Analog (in 2 channels, out 1 channel)
 - G7F-ADHB *2): Analog (in 2 channels, out 2 channels)
 - G7F-ADHC *2): Analog (in 2 channels, out 1 channel)
- RTD
 - G7F-RD2A *2): RTD 4 channels
- Analog timer
 - G7F-AT2A: Analog timer (4 points)

Communication unit *3)

- G7L-CUEB: RS-232C 1 channel
- G7L-CUEC: RS-422 1 channel
- G7L-FUEA: Fieldbus I/F (Fnet master)
- G7L-RUEA: Fieldbus I/F (Rnet master)
- G7L-DBEA: DeviceNet (slave)
- G7L-PBEA: Profibus-DP (slave)

Option pack

- G7E-RTCA: RTC (Real timer clock) pack
- G7E-M256B: Memory pack
(for program back-up)

*1) I/O assignment is the same as that of GM7.

*2) GM7U only. And stands for a slim type

*3) Built-in RS-232C and a communication module shares the same communication port (CH0) and you are not able to use them at the same time. In case of GM7U, you are able to use built-in RS-485 (CH1) and a comm. module (CH0) at the same time.

GLOFA-GM6

Programmable Logic Controller



■ Features

- High performance features with compact size
- High-speed processing using dedicated CPU
- Designed by international standard language (IEC61131-3): IL, LD, SFC
- Max. I/O points: 384 points



■ Specifications

GM6		GM6-CPUA	GM6-CPUB	GM6-CPUC	Remark
Operation method		Cyclic execution of stored program, Time-driven operation, Internal task operation			
I/O control method		Scan synchronized batch processing method (Refresh method)			
Program language		IL (Instruction list) / LD (Ladder diagram) / SFC (Sequential function chart)			
Number of Instructions	Operator	LD: 13, IL: 20			
	Standard function	194			
	Standard function block	12			
	Special function block	Each special module has its own special function block			
Processing speed	Operator	0.5 μ s/instruction			
	Standard function	0.5 μ s/step			
	Standard function block				
Programming memory capacity		68K			Built-in flash memory (128K)
I/O points	With 32-pt modules	192 points			
	With 64-pt modules	384 points			
	With remote I/Os	512 points			
Data memory	Direct variable area (DVA)	2~8K			Setting in GMWIN
	Symbolic variable area (SVA)	30K - Direct variable area			
Timer		No limitation. Time range: 0.001~4294967.295 sec (1193 hours)			20 bytes per 1 timer in SVA
Counter		No limitation. Count range: -32,768~32,767			8 bytes per 1 counter in SVA
Operation mode		RUN, STOP, PAUSE, DEBUG			
Data retention at power failure		Set to 'Retain' at data declaration			
Number of program blocks		100			
Program type	Scan	100 - (Number of program blocks in task)			
	Time-driven	8			
	External interrupt	8			
	Internal	8			
	Initialization	1 (_INIT)			8 in total
Self-diagnostic functions		Watchdog timer, Memory error, I/O error, Battery error, Power supply error			
Restart mode		Cold, Warm			
Base type		4/6/8/12 slot *1)			Expansion is not available
Built-in functions		<ul style="list-style-type: none"> • Cnet (RS-232C) *2) • PID control • Cnet (RS-422/485) • RTC function 			
Internal current consumption		170mA			170mA

*1) In case of GM6-B12M, the module installed in slot number 8 or later is designated as base number 1 and slot number 0 or later; the suitable power module for GM6B12M is GM6-PAFC, which can't support an analogue module. For analog modules or TC module, you are supposed to use GM6-PAFB or GM6-PDFB considering internal current consumption of each module.

Communication modules are not to be installed in after slot number 7.

*2) Built-in RS-232C port: 4 (Rx), 7 (Tx), 5 (SG)

GLOFA-GM6


Programmable Logic Controller

Input modules

■ Input module specifications

Input type		DC Input					AC Input *1)					
Part number		G6I-D21A	G6I-D22A	G6I-D22B	G6I-D24A	G6I-D24B	G6I-A11A	G6I-A21A				
Input point		8 points	16 points		32 points		8 points					
Rated input voltage		DC12/24V	DC12/24V	DC24V	DC12/24V	DC24V	AC100~120V	AC200~240V				
Rated input current		3/7mA	3/7mA	7mA	3/7mA	7mA	7mA	11mA				
On voltage/current		DC9.5V or more/ 3.5mA or more	DC9.5V or more/ 3.5mA or more	DC15V or more/ 4.3mA or more	DC9.5V or more/ 3.5mA or more	DC15V or more/ 4.3mA or more	AC80V or more/ 5mA or more	AC80V or more/ 5mA or more				
Off voltage/current		DC5V or less/ 1.5mA or less	DC5V or less/ 1.5mA or less	DC5V or less/ 1.7mA or less	DC5V or less/ 1.5mA or less	DC5V or less/ 1.7mA or less	AC30V or less/ 2mA or less	AC30V or less/ 2mA or less				
Response time	Off→On	5ms or less	5ms or less	5ms or less	5ms or less	5ms or less	15ms or less	15ms or less				
	On→Off	5ms or less	5ms or less	5ms or less	5ms or less	5ms or less	25ms or less	25ms or less				
Common		8 points/COM			32 points/COM		8 points/COM					
Operating indicator		LED										
Insulation method		Photocoupler insulation										
Current consumption (DC5V)		40mA	70mA		75mA		35mA					

*1) AC input modules: 50/60Hz




* Refer to user's manual for wiring.

Output modules

■ Output module specifications

Output module type		Relay output			Transistor output					
Part number		G6Q-RY1A	G6Q-RY2A	G6Q-RY2B	G6Q-TR2A	G6Q-TR2B	G6Q-TR4A	G6Q-TR4B		
Output point		8 points	16 points		16 points	16 points	32 points	32 points		
Rated load voltage	DC12/24V, AC110/220V (50/60Hz)			DC12/24V			AC110/220V (50/60Hz)			
Off leakage current				0.1mA or less			2.5mA or less			
On voltage drop	-			DC1.5V or less	DC2.5V or less	DC3V or less	AC1.5V or less			
Rated load current	1 Point	2A			0.5A	0.1A	1A			
current	1 Common	-	5A		3A	2A	4A			
Response time	Off → On	10ms or less			2ms or less			1ms or less		
	On → Off	12ms or less			2ms or less			0.5cycle+1ms or less		
Common	1 point/COM		8 points/COM	16 points/COM		32 points/COM	8 points/COM			
Operating indicator	LED									
Insulation method	Relay				Photocoupler					
Surge absorber	-	Varistor		Clamp diode		Varistor, CR absorber				
Current consumption (DC5V)	210mA	400mA		180mA	170mA	140mA	145mA	190mA		
External power supply	-	DC24V								

* G6Q-TR2A/TR4A: Sink type, G6Q-TR2B/TR4B: Source type



* Refer to user's manual for wiring.




GLOFA-GM6

Programmable Logic Controller

■ I/O hybrid module specifications

G6H-DR2A			
Input		Output	
Input point	8 points	Output point	8 points
Insulation method	Photocoupler	Insulation method	Relay
Rated input voltage	DC 12/24V	Rated load	DC 24V, 2A (Resistance)/1 point, 4A/COM voltage/current AC 220V, 2A ($\text{COS } \phi = 1$)/1 point, 4A/COM
Rated input current	3/7mA	Min. load voltage/current	DC 5V/1mA
Operating voltage range	DC 10.2~28.8V (Ripple rate < 5%)	Max. load voltage	AC 250V, DC 125V
Max. simultaneous input	8 points (100% simultaneous ON)	Off leakage current	0.1mA (AC 220V, 60Hz)
On voltage/current	DC 9.5V/3.5mA or more	Max. switching frequency	1,200 times/hour
Off voltage/current	DC 5V/1.5mA or less	Surge absorber -	
Input impedance	About 3.3 kΩ	Service life	20 million times or more
Response time	Off → On 5ms or less On → Off 7ms or less -	Mechanical	100,000 times or more (Rated load V/C)
Common	8 points/COM	Response time	Off → On 10ms or less On → Off 12ms or less
Operating indicator	LED	Common	8 points/COM
External connection		Operating indicator	LED
Current consumption (DC 5V)		18-point terminal block connector (M3 × 6 screws)	
Weight		250mA	
		200g	



* Refer to user's manual for wiring.

GLOFA-GM4

Programmable Logic Controller



■ Features

- Max. I/O points: GM4A/B (2,048), GM4C (3,584)
- Fast processing time with high-speed gate array
- Fit for small- and medium-sized manufacturing line network
- In case of remote system configuration, large-scale control available
- Cnet, DeviceNet, Fast Ethernet, Fnet, Profibus-DP, Rnet support
- Downsizing and high performance/function
- Special function modules
 - Analog I/O, PID, High-speed counter, Position control (APM), AT, TC, RTD, etc



■ Specifications

GM4	GM4-CPUA	GM4-CPUB	GM4-CPUC	Remark	
Operation method	Cyclic execution of stored program, Time-driven operation, Internal task operation				
I/O control method	Scan synchronized batch processing method (Refresh method)				
Program language	IL (Instruction list) / LD (Ladder diagram) / SFC (Sequential function chart)				
Number of Instructions	Operator	LD: 13, IL: 20			
	Standard function	194	194+ 'Real number function'		
	Standard function block	12			
	Special function block	Each special module has its own special function block			
Processing speed	Operator	0.2 μ s/instruction	0.12 μ s/instruction		
	Standard function	0.2 μ s/step	0.12 μ s/step		
	Standard function block				
Real number operation	No	Yes			
Programming memory capacity	128K (32Ksteps)	1M			
I/O points	With 32-pt modules	1,024 points	1,792 points		
	With 64-pt modules	2,048 points	3,584 points		
	With remote I/Os	4,096 points	8,192 points	32,768 points	
Data memory	Direct variable area (DVA)	2~16K	8~64K	Setting in GMWIN	
	Symbolic variable area (SVA)	52K-Direct variable area	428K-Direct variable area		
Timer	No limitation. Time range: 0.001~4294967.295 sec (1193 hours)				
Counter	No limitation. Count range: -32,768~32,767				
Operation mode	RUN, STOP, PAUSE, DEBUG				
Data retention at power failure	Set to 'Retain' at data declaration				
Program type	Scan	180 (Number of program blocks) - (Program blocks in task)			
	Time-driven	8	32		
	External interrupt	8			
	Internal	16			
	Initialization	2 (_INIT, _H_INIT)			
	Error	None	1 (_ERR_SYS)		
Self-diagnostic functions	Watchdog timer, Memory error, I/O error, Battery error, Power supply error				
Restart mode	Cold, Warm, Hot				
Flash memory	External (128K)	Built-in (512K)	Built-in (6M)	OPUC: Program 1M, Upload 5M	
Program port	RS-232C		RS-232C, USB		
Maximum expansion stage	3		6 *		
Internal current consumption	130mA				

K: kilobyte

* For 6 stage expansion you need to use special base (main, expansion) and special expansion cable. Refer to P26 and P65, please.




GLOFA-GM4

Programmable Logic Controller

Configuration

■ GMWIN programming with IL, LD, and SFC



*1) GM4-CPUB and GM4-CPUC have a built-in flash memory that you can't use memory module.

*2) In case of GM4-B12M, you can't extend I/O modules; the base and slot number of from slot number 8 to 11 is set as base number 1, slot number from 0 to 3.

In case of GM4-CPUA, you can't install a communication module after slot number 8.

Input/output modules

■ Features

- 16/32/64 points
- Operation status monitoring by LED
- Insulated by Photocoupler
- Easy maintenance with terminal block & one touch installation

■ Input module specifications

Input type		DC Input			
Part number	G4I-D22A/C *1)	G4I-D22B	G4I-D24A/C *1)	G4I-D24B	G4I-D28A *2)
Input point	16 points		32 points		64 points
Rated input voltage		DC 12/24V *1)			
Rated input current	5/11mA		3/7mA		3/6mA
On voltage/current	DC 9.5V or more/4mA or more		DC 9.5V or more/3mA or more		
Off voltage/current		DC 6V or less/1.0mA or less			
Response time	Off → On On → Off		10ms or less 10ms or less		
Common	8 points/COM		32 points/COM		
Type	Source/Sink Source (+COM)		Source/Sink LED	Source (+COM)	Source/Sink
Operating indicator					
Insulation method	Photocoupler insulation				
Current consumption (DC 5V)	70mA		75mA		250mA
Input type		AC Input			
Part number	G4I-A12A	G4I-A22A			Interrupt
Input point	16 points				G4F-INTA
Rated input voltage	AC 100~120V (50/60Hz)	AC 200~240V (50/60Hz)			8 points DC 24V
Rated input current	11mA				10mA
On voltage/current	AC 80V or more/6mA or more	AC 150V or more/4.5mA or more			DC 15V or more
Off voltage/current	AC 30V or less/3mA or less	AC 50V or less/3mA or less			DC 5V or less
Response time	Off → On On → Off	15ms or less 25ms or less			0.5ms or less 0.5ms or less
Common	8 points/COM				1 point/COM
Operating indicator		LED			
Insulation method	Photocoupler insulation				
Current consumption (DC 5V)		70mA			

■ Output module specifications

Output type		Transistor output			
Part number	G4Q-TR2A	G4Q-TR2B	G4Q-TR4A	G4Q-TR4B	G4Q-TR8A
Output point	16 points		32 points		64 points
Rated load voltage			DC 12/24V		
Rated load current	1 Point 1 Common	0.5A 3A/COM		0.1A 2A/COM	
Response time	Off → On On → Off		2ms or less 2ms or less		
Common	8 points/COM		32 points/COM		
Operating indicator		LED			
Type	Sink (-COM) Source (+COM)		Sink (-COM) Photocoupler insulation	Source (+COM)	Sink (-COM)
Insulation method					
Surge absorber	Varistor			-	
Current consumption (DC 5V)	100mA		160mA		250mA
External power supply		DC 24V			
Output type		Relay output			
Part number	G4Q-RY2A *3)		G4Q-SS2A		G4Q-SS2B
Output point		16 points			
Rated load voltage	DC 12/24V, AC 110/220V (50/60Hz)		AC 100~240V (50/60Hz)		
Rated load current	1 Point 1 Common	2A 4A/COM	1A 5A/COM		0.6A 2.4A/COM
Response time	Off → On On → Off	10ms or less 12ms or less		0.5cycle +1ms or less 0.5cycle +1ms or less	
Common		8 points/COM			
Operating indicator		LED			
Type		-			
Insulation method	Photocoupler insulation				
Surge absorber	-		Varistor, CR absorber		
Current consumption (DC 5V)	100mA		330mA		
External power supply	DC24V		-		

*1) Rated input voltage for G4I-D2XC is DC24V and on voltage is 19.6V

*2) G4I-D28A and G4Q-TR8A are connector-type modules










*3) For G4Q-RY2A operation, you need to supply DC24V.

GLOFA-GM4

Programmable Logic Controller

Input/output modules

■ Wiring diagram for input modules


G4I-D22A/C *1)  <p>Terminal block No.</p>	G4I-D22B  <p>Terminal block No.</p>	G4I-D24/ *1)  <p>Pin No.</p>
G4I-D24B  <p>Pin No.</p>	G4I-D28A *2)  <p>Pin No.</p>	
G4I-A12A  <p>AC110V</p> <p>Terminal block No.</p>	G4I-A22A  <p>AC220V</p> <p>Terminal block No.</p>	G4F-INTA  <p>Terminal block No.</p>

*1) Rated input voltage for G6I-D2XC is DC24V and on voltage is 19.6V.

*2) G4I-D28A is a connector-type module.

* Refer to user's manual for wiring.

■ Wiring diagram for output modules



*1) G4Q-TR8A is a connector type module.

*2) For G4Q-RY2A operation, you need to supply DC24V.

* Refer to user's manual for wiring.

GLOFA-GM4


Programmable Logic Controller

■ I/O hybrid module specifications

Input type		DC Input			
Part number		G4H-DT2A			
Input point		8 points			
Rated input voltage		DC 12V	DC 24V	DC 12V	DC 24V
Rated input current		5mA	11mA	5mA	11mA
On voltage/current		DC 9.5V or more/4.0mA or more			
Off voltage/current		DC 6V or less/1.0mA or less			
Response time	Off → On	10ms or less			
	On → Off	10ms or less			
Common		8 points/1COM			
Operating indicator		LED			
Insulation method		Photocoupler insulation			
Current consumption(DC 5V)		100mA			

Output type		Transistor output	Relay output
Part number		G4H-DT2A	G4H-DR2A
Output point		8 points	
Rated load voltage		DC 12/24V	DC 24V/AC 220V (50/60Hz)
On voltage drop		DC 1.5V or less	-
Off leakage current		0.1mA or less	
Rated load current	0.5A/1 point	2A/1 point	
	3A/COM	5A/COM	
Response time	Off → On	2ms or less	10ms or less
	On → Off	2ms or less	10ms or less
Common		8 points/1COM	
Operating indicator		LED	
Insulation method		Photocoupler insulation	
Surge absorber	Varistor	-	


■ Wiring diagram



*1) For G4H-DR2A operation, you need to supply DC24V.

* Refer to user's manual for wiring.

System configuration



*1) Refer to P42, please.

GLOFA-GM Fast Enet (Ethernet) system

Programmable Logic Controller

■ Features

- 10/100BASE-TX, 100BASE-FX (optical), 10BASE-5 support
- High reliability and performance with 32-bit processor
- Open (Information level) Ethernet and LSIS dedicated (Between LS PLCs) Ethernet: 2 types
- User-defined protocol editing and connection to other system using function block: Open-type (-EUxB) only
- GMWIN service for remote programming, remote monitoring and PLC mode control



Specifications

■ Open Ethernet

Item	GxL-EUTB	GxL-EUFB *1)	GxL-EU5B
Network	10/100BASE-TX, UTP (TP)	100BASE-FX, Fiber optic	10BASE-5, AUI
Support protocol		TCP/IP, UDP/IP	
Service	With LS PLCs With other devices Application	High-speed link, Command service Command service GMWIN service, Dedicated protocol service	
Communication data		60 words/block or 200 words/block, 1446 bytes/frame	
Number of channels	16		
Usage		Communication between LS PLC and other devices (PC), High-speed link between LS PLCs	
Applicable type		GM6/GM4	GM4

■ Dedicated Ethernet


Item	Master	GxL-EUTC	GxL-EUFC *1)	GxL-EU5C
	Slave	GxL-ERTC	GxL-ERFC *1)	GxL-ER5C
Network		10/100BASE-TX, UTP (TP)	100BASE-FX, Fiber optic	10BASE-5, AUI
Support protocol			Token passing	
Service	With LS PLCs With other devices Application		High-speed link, Command service -GMWIN service	
Communication data			200 words/block	
Number of connecting stations			64	
Usage			High-speed link between LS PLCs	
Applicable type		GM6/GM4		GM4

*1) SC-type connector is used.

GLOFA-GM Ethernet system configuration

Programmable Logic Controller

System configuration



GLOFA-GM Fnet system configuration

Programmable Logic Controller

■ Features

- Transmission speed: 1Mbps, transmission distance: 750m (Electric) *1)
- Communication available up to 5.25km with repeaters (Max.: 6): Electric *1)
- High-speed link capacity: Max. 61,440 points
- Convenient to configure various multi-drop network systems with remote I/O modules (G4L-RBEA/G6L-RBEA)

*1) In case of fiber optical cable, transmission distance is 3km and max. distance is 21km with 6 repeaters.



■ Specifications

Item	Electrical module	Optical module
Transmission speed	1Mbps	
Encoding type	Manchester Biphase-L	
Transmission distance (per segment)	Max. 750m	Max. 3km
Max. extension distance	Max. 5.25km (6 repeaters)	Max. 21km (6 EOCs)
Transmission medium	Twisted pair cable	Optical cable
Number of nodes	64	
Communication method	Circulated token passing, Address prove method	
High-speed link	Max. data size/station	61,440 points (3840 words)
	Max. sending data size	30,720 points (1920 words)
	No. of data block in transmission	64 blocks
	Data block size in transmission	60 words
Comm. module	GM4	G4L-FUEA
	Local	G6L-FUEA
	GM6	-
	GM7/GM7U	G7L-FUEA *1)
	Remote	G4L-RBEA
Others	GM4	G6L-RBEA
	GM6	-
		<ul style="list-style-type: none"> Local module is to be set in the I/O slot of the main base. Remote module is to be set in the CPU slot of the main base. GM4-CPUA: 2, GM4-CPUB: 4, GM4-CPUC: 8 GM6: 2 *2) GM7/GM7U: 1

*1) You are not able to use the built-in Cnet or other communication unit when you use G7L-FUEA.

*2) GM6: Up to 2 Fnet modules, GM7/GM7U: Only 1 communication module

*3) GOL-FREB: AC 110~220V, GOL-FREC: DC 24V

Fieldbus active coupler (GOL-FACA)	
Transmission speed	1Mbps
Cable	Optical cable
Transmission distance	3km
Function of signal regeneration	Regenerating, Reshaping function
On reception of abnormal data	Error data transmission
Frame error check	CRC 16
Max.number of coupling station	8
Power supply	AC110V/220V, DC24V
Coupling optic card	Rack type (Branch off/ select the number of stations)
Fieldbus repeater (GOL-FREB, FREC) *3)	
Transmission speed	1Mbps
Cable	Shielded twisted pair cable
Max. extension distance	750m per module
Max. number of repeaters	6 units between stations
Max. distance	5.25km between stations (when 6 repeaters used)
On reception of abnormal data	Error data transmission
Frame error check	CRC 16
Fieldbus electric/optical converter (GOL-FOEA)	
Transmission speed	1Mbps
Cable	Optical cable, Shielded twisted pair cable
Max. transmission distance	3km
Function of signal regeneration	Regenerating, Reshaping
On reception of abnormal data	Error data transmission
Frame error check	CRC 16

■ Network cable

Item	Specifications	Maker
Shielded twisted pair cable	LIREV-AMESB 2 x 1mm, 18 AWG LIREV-AMESB 2 x 0.64mm, 22 AWG	LS CABLE CO., LTD
Optical cable	Y220909, Multi-mode, ST type OJC-DP-MM-XX-ST-ST (XX = Number in meter), Multi-mode, ST type	LS CABLE CO., LTD
Terminal resistance	110 Ω, 1/2 Watt	-


* The above cables are used in development and performance test.

And we can't guarantee system performance as is shown in user's manual, if you use other cables.


GLOFA-GM Fnet system configuration

Programmable Logic Controller



System configuration



Fnet cable connection



Terminal resistance



GLOFA-GM Cnet (Computer link system)

Programmable Logic Controller

■ Features

- Various protocol communication thanks to Frame Editor and command
- Easy to make a communication program
- GMWIN connection via phone line using an external modem connection
- Long-distance communication via phone line using a dedicated line modem connection
- Up to 32 stations connectable: Multi-drop service of LSIS dedicated protocol
- RS-232C/RS-422 communication port (Interlocking/Standalone mode)
- Various communication speed setting (300~76,800bps) *1)
- Parameter setting in Frame Editor
- Full duplex and half duplex support
- GM4-CPUC: 8, GM4-CPUA/B: 4
- GM6: 4
- GM7/GM7U: Only 1 communication module
- Remote operating mode change in online mode
- Easy interface with other PLCs due to AB DF1/MODBUS communication driver support (Slave)
- Easy upgrade using flash memory: Cnet version 2.0 or later



■ Operation mode

Operation mode	Remark
GMWIN mode	Program download, upload by GMWIN protocol (RS-232C)
Dedicated protocol	Data communication using LSIS dedicated protocol
User-defined protocol	Data communication using user-defined frame and command
Test mode	Self-diagnosis (except GM7/GM7U)


■ Specifications

Item	G4L-CUEA	G6L-CUEB	G6L-CUEC	G7L-CUEB	G7L-CUEC									
Interface	RS-232C, RS-422/485	RS-232C	RS-422/485	RS-232C	RS-422/485									
Comm. mode	Dedicated	1:1 or 1:N communication using LSIS dedicated mode												
	GMWIN	Program download, upload and remote control using GMWIN protocol (RS-232C, 1:1)												
	User-defined	Communication using user-defined protocol by Frame Editor (Interface with other PLCs)												
Data form	Start bit	1 *2)												
	Data bit	7 or 8 *2)												
	Stop bit	1 *2) or 2												
	Parity bit	Even / odd / none												
Channel selection	By mode switch	-												
Synchronization	Asynchronous													
Transmission speed	300/600/1,200/2,400/4,800/9,600/19,200/38,400/76,800 *1)													
Network configuration	1:1, 1:N, N:M available (N≤31)	1:1	1:1, 1:N	1:1	1:1, 1:N									
Modem communication	Available through RS-232C													
Transmission	RS-232C	15m (Extendible using a modem)	15m	-	15m									
	RS-422/485	500m	-	500m	500m									
Max. number of installation	GM4C: 8, GM4A/B: 4	4												
Diagnostic function	Loop-back test mode													
Current consumption (DC 5V)	160mA													
*1) Default value														
*2) RS-232C: 300~38,400bps, RS-422/485: 300~76,800bps, In case of MODBUS communication, baud rate is 2,400~38,400bps														
*3) If you use G7L-CUEB or G7L-CUEC, which is not available to use in G7M-DR10A/DS) or G7M-DT10A, you are not able to use built-in Cnet or any other communication module.														


GLOFA-GM Cnet (Computer link) system configuration

GLOFA GM Series


■ Communication with RS-422/485 devices





■ 1:1 and N:M connection (dedicated + user-defined)



■ MODBUS



■ Cnet cable connection (RS-232C)



GLOFA-GM Dnet (DeviceNet system)

Programmable Logic Controller

■ Features

- Real time control of various I/O devices in network system
- Max. 63 slave modules control with one master module
- Flexibility in network configuration: Multi-drop and T branch connection
- Connectable to other master module and various slave modules
 - Communication with other slave modules as master
 - Communication with other master module as slave
(Mode change by mode switch in master module)
- GM4-CPUC: 8, GM4-CPUB: 4, GM4-CPUA: 2
- GM6: 2
- GM7/GM7U: 1 slave module
- Master/slave communication as predefined master/slave connection communication using scan list enabling high-speed link without other configuration tool



■ Specifications

Item	G4L-DUEA	G6L-DUEA	G7L-DBEA
Module type	Master/Slave (setting by dip switch)		Slave
Protocol	CAN		
Transmission distance and speed *1)	Communication speed	Max. network length (Drop cable)	Max. drop cable length
	500kbps	100m	6m or less
	250kbps	250m	6m or less
Max. number of stations	125kbps	500m	6m or less
		64	156m
Cable	DeviceNet cable: 5 wires (Signal: 2 wires, power: 2 wires, shield: 1 wire)		
Bus type	Multi slave / Multi casting		
	1:1 (Peer-to-peer type)		
	Poll, Strobe, COS/Cyclic type *2)		
Max. node number	Max. 64 MAC ID (Max. 2,048 points)		
System features	Available to insert/remove a node when power is on		
Diagnostic function	Duplicated station/CRC error check, Abnormal station detection, Usage of scan list, LED (operation)		
Current consumption (DC5V)	285mA	230mA	250mA

*1) In case of thin cable, the max. distance is within 100m regardless of transmission speed.

*2) The type of Strobe, COS/Cyclic on bus type will be served later.

* Maximum transmission distance when thick and thin cables coexist.


The table below lists both the maximum transmission distance when thick and thin cables coexist.

Communication speed	Maximum transmission distance of trunk line when thick and thin cables coexist
125kbps	Thick cable length + 5 × thin cable length ≤ 500m
250kbps	Thick cable length + 2.5 × thin cable length ≤ 250m
500kbps	Thick cable length + thin cable length ≤ 100m


GLOFA-GM Dnet system configuration

Programmable Logic Controller

System configuration



■ System configuration with other products



*1) Refer to P42, please.

GLOFA-GM Pnet (Profibus-DP system)

Programmable Logic Controller

■ Features

- Profibus-DP (Decentralized periphery)
- Low cost network appropriate to field level
- Proper to communicate among a master automation device and distributed slave I/O devices
- Master slave network
- Fast slave communication omitting application layer
- Based on RS-485 communication as transmission medium
- Communication speed: 9.6kbps~12Mbps
- Communication distance: 100~1,200m
- Max. 126 stations (32 stations/segment) support
- Network setup using Sycon (Configuration tool)
- Transmission data of master: 1K~7K
- Communication using high-speed link parameter




■ Specifications

Item	G4/6L-PUEA	G4/6L-PUEB	G7L-PBEA	Remark
Module type	Master	Slave		Class 1
Network	Profibus-DP			
Protocol	EN 50170/DIN 19245			
Interface	RS-485 (Electric)			
Medium access	Token passing & poll	Poll		
Topology	Bus			
Modulation	NRZ			Asynchronous
Cable	Shielded twisted pair cable			
	1,200m (9.6kbps~187kbps)			
Transmission distance	400m (500kbps)			
	200m (1.5Mbps)			
	100m (3M~12Mbps)			
Max. number of slave/network	126			
Max. number of slave/segment	32			
Dual port memory size	1K	7K	128 bytes	
Max. I/O data	In: 512 bytes Out: 512 bytes	In: 3584 bytes Out: 3584 bytes	In: 64 bytes Out: 64 bytes	
Communication parameter setting	High-speed link parameter in GMWIN		GMWIN	
Configuration tool	Sycon-PB			
Configuration port	RS-232C Configuration port support		-	
Current consumption (DC 5V)	560/520mA	670/700mA	350mA	

GLOFA-GM Pnet system configuration

Programmable Logic Controller

System configuration



*1) Refer to P42, please.

SMART I/O

Programmable Logic Controller

■ Features

- Reduction in the amount of wiring
- Real-time control of distributed I/O devices
- Rnet, Profibus-DP, DeviceNet, Modbus (RS-422/485) support
- Various I/O modules (DT, TR)
 - A: Sink (NPN), fixed terminal block, 0.1A (Rated load current)
 - B: Source (PNP), fixed terminal block, 0.5A (Rated load current)
 - C: Source (PNP), removable terminal block, 0.5A (Rated load current)
 - A1: Sink (NPN), fixed terminal block, 0.5A (Rated load current)
 - C1: Sink (NPN), removable terminal block, 0.5A (Rated load current)



■ Specifications

Item		Input		Output		Mixed Input/output	
		DC (Sink/Source)		TR (Sink)		DC (Sink/source)	TR (Sink)
Point		16	32	16	32	16	16
Rated input (Load voltage)		DC 24V		DC 24V		DC 24V	DC 24V
Rated input current *1) (Load current)		7mA		0.1A/2A		7mA	0.1A/2A
Response time	Off → On	Under 3ms		Under 0.5ms		Under 10ms	Under 0.5ms
	On → Off	Under 3ms		Under 1ms		Under 10ms	Under 1ms
Common (Point/COM)		16/COM		16/COM		8/COM	16/COM
Supporting network & part number	Rnet	GRL-D22A	GRL-D24A	GRL-TR2A	GRL-TR4A	GRL-RY2A	GRL-DT4A
	Profibus-DP	GPL-D22□ *2)	GPL-D24□	GPL-TR2▲ *3)	GPL-TR4▲	GPL-RY2□	GPL-DT4▲
	DeviceNet	GDL-D22□	GDL-D24□	GDL-TR2▲	GDL-TR4▲	GDL-RY2□	GDL-DT4▲
	Modbus	GSL-D22A	GSL-D24A	GSL-TR2A	GSL-TR4A	GSL-RY2A	GSL-DT4A

*1) It is for A type. For other types, refer to Features.

*2) □: A, C (A: Fixed terminal block, B: Removable terminal block)

*3) ▲: A, A1, B, C, C1


■ Field network support

Item	Rnet (LS SMART I/O)	Profibus-DP	DeviceNet	Modbus
Protocol	LSIS Dedicated Rnet protocol (Fnet for remote)	Profibus-DP (RS-485/EN50170)	DeviceNet (CAN)	Modbus (RS422/485) *1)
Transmission speed	1Mbps	9.6kbps~12Mbps	125/250/500kbps	2.4kbps~38.4kbps
Transmission distance	750m/segment	100m~1.2km	500/250/125m(Thin cable: 100m)	500m
Topology	Bus token	Bus	Trunk & drop	Bus
Transmission method	Token pass & Broadcast	Token pass & Master/Slave (Poll)	CSMA/NBA *2) (Poll, Cyclic, COS, Strobe)	Master/Slave (Poll)
Max. number of stations	64/segment (In 32/Out 32)	32/segment	64	32
Link capacity	2,048 pt./master (64 sta. × 32 pt.)	1K* master: -PUEA 7K* master: -PUEB	2,048 pt./master	64 pt./station

*1) RS-485 is available at Modbus SMART I/O version 1.1 or later.

*2) Carrier Sense Multiple Access with Non-destructive Bitwise Arbitration.

■ Dimensions




*1) The dimensions of relay type SMART I/O is equivalent to those of 32-point SMART I/O.

*2) C, C1 type: 47.5

SMART I/O system configuration


Programmable Logic Controller

■ SMART I/O Rnet system




*1) GOL-GWRA: Rnet remote connection module

■ SMART I/O MODBUS system




*2) RS-485 is available at SMART I/O version 1.1 or later.

■ SMART I/O Profibus-DP system



*3) Segment: communication section where a repeater or other master station is not used.

SMART I/O DeviceNet system



Analog input module (GM4/6)

Programmable Logic Controller

■ Features

- 4-/8-channel analog input per module
- Voltage/Current selection by dip switch/terminal
- Digital range selection (-8,192~8,191 or -192~16,191): G4F-AD2A
- High resolution (1/16,000, 1/4,000)



■ Specifications


Item		G4F-AD2A *1)	G4F-AD3A	G6F-AD2A *2)
Analog input	Voltage	DC -5~+5 DC -10~+10V	DC 1~5V DC 0~10V	DC 1~5V DC 0~10V, -10~+10V
	Current *3)	DC 20~+20mA	DC 4~20mA	DC 4~20mA
	Voltage/Current select	Input terminal connection	Input selection switch	Input terminal connection
	Voltage range select	Input range selection switch	Program	Input range selection switch
Digital output		0~16,000 -8,000~8,000	0~4,000	0~4,000 -2,000~2,000
Resolution	DC 1~5V	-	1.0mV (1/4,000)	1.0mV (1/4,000)
	DC 0~10V	-	2.5mV (1/4,000)	2.5mV (1/4,000)
	DC -5~5V	0.625mV (1/16,000)	-	-
	DC -10~10V	1.25mV (1/16,000)	-	5mV (1/4,000)
	DC 20~20mA	2.5μA (1/16,000)	-	-
	DC 4~20mA	-	4μA (1/4,000)	4μA (1/4,000)
Accuracy		±0.5% (Full scale) ±0.3% at 25°C	±0.5% (Full scale) ±0.3% at 25°C	±0.5% (Full scale) ±0.3% at 25°C
Max. conversion speed		5ms/Ch	5ms/Ch	5ms/Ch
Max. absolute output	Voltage	±12V		
	Current	±25mA		
Analog input point		4 Channels	8 Channels	4 Channels
Offset/gain		Available	Not available	
Insulation method		Between input terminal and PLC power supply: Photocoupler, Between channels: No insulation		
Current consumption		400mA (5V)	500mA (5V)	40mA (+5V), 50mA (+15V), 20mA (-15V)

*1) You are able to adjust offset and gain value in G4F-AD2A so that you can adjust input range.


*2) If you use analog modules in GM6, you are supposed to use GM6-PAFB or GM6-PDFB for power module.

*3) For current input, connect V and I terminal.

■ A/D conversion characteristics



■ Configuration



Analog output module (GM4/6)

Programmable Logic Controller

■ Features

- 2-/4-/8-channel analog output per module
- Analog voltage/current output when CPU stops (set in FB)
 - medium, previous, max., min. value: G4F-DA1A
- Various modules according to output types



■ Specifications



Item	G4F-DA1A *1)	G4F-DA2V	G4F-DA3V	G4F-DA2I	G4F-DA3I *2)	G6F-DA2V *3)	G6F-DA2I *3)
Digital input	-192~16,191 -8,092~8,191				-48~4047		
Analog output	Voltage	DC -10~10V	DC -10~10V	-	-	DC -10~10V	-
	Current	DC 4~20mA	-	-	DC 4~20mA	-	DC 4~20mA
	V/C selection	Output terminal	-	-	-	-	-
Resolution	DC -10V~10V	1.25mA (1/16000)	5mV (1/4000)	-	-	5mV (1/4000)	-
	DC 4~20mA	2.5μA (1/6000)	-	-	4μA (1/4000)	-	4μA (1/4000)
Accuracy	±0.3% (Full scale)				±0.5% (Full scale)		
Max. conversion speed	3ms/module	10ms/module	15ms/module	10ms/module	15ms/module	10ms/module	
Max. absolute output	Voltage	DC 15V			-	DC 15V	-
	Current	DC 24mA	-	-	DC 24mA	-	DC 24mA
Analog output point	2 Channels	4 Channels	8 Channels	4 Channels	8 Channels	4 Channels	
Insulation	Between input terminal and PLC power supply: Photocoupler, Between channels: No insulation						
External power supply	Voltage	-	-	-	DC 21.6~26.4V	-	-
	Current	-	-	-	230mA	-	-
Current consumption		450mA (5V)	400mA (5V)	700mA (5V)	680mA (5V)	70mA	5V (40mA) 5V (80mA) -15V (60mA)
							5V (40mA) 15V (120mA) -15V (25mA)

*1) You are able to adjust offset and gain value in G4F-DA1A so that you can adjust output range.

*2) If you use G4F-DA3I, you are supposed to supply external DC 24V for its operation.

*3) If you use analog modules in GM6, you are supposed to use GM6-PAFB or GM6-PDFB for power module.

■ A/D conversion characteristics



Temperature control module (GM4)

Programmable Logic Controller

■ Features

- Simultaneous control of different processors with one module
- Forward/Reverse control selectable
- Manual output (forced output) available
- Autotuning (P, I, D values are found automatically)
- No additional input/output is needed due to various input/output built-in functions
- Input: RTD (2 types), Thermocouple (7 types), Voltage, Current
- Output: Current, Open collector output of time proportional control
- Cascade function: Interworking control of a processor
- On/Off control available



■ Specifications (G4F-TMCA)

● Input/output specifications

Item			Specifications				
Input	Thermocouple	Type	DIN specification	BS specification	Measuring temperature range (°C)	Measuring voltage range (µV)	
		K	NiCr-Ni	NiCr-NiAl	-200.0~1,300.0	-5,891~52,398	
		J	-	Fe-CuNi	-200.0~1,000.0	-7,890~57,942	
		E	-	NiCr-CuNi	200.0~800.0	-8,824~61,022	
		T	-	Cu-CuNi	-200.0~400.0	-5,603~20,869	
		B	-	PtRh30-PtRh6	400.0~1,800.0	0~20,215	
		R	-	PtRh13-Pt	0.0~1,750.0	0~17,942	
	RTD	S	PtRh-Pt	PtRh10-Pt	0.0~1,750.0	786~13,585	
		Type			Measuring temperature range (°C)	Measuring resistance range (Ω)	
		Pt100			-200.0~600.0	18.49~313.59	
		JPt100			-200.0~600.0	17.14~317.28	
Output	Analog	Input range	I V		DC 4~20mA DC 1~5V		
		Max.resolution	I V		2µA (1/8,000) 0.25mV (1/8,000)		
		Absolute Max. input			Voltage: 15V, Current: 25mA		
		Insulation method			Between input terminal and PLC power supply: Photocoupler, Between channels: No insulation		
		Number of loops			2 (Simultaneous 2 loops, including thermocouple, RTD, V and I input, available to use)		
	Digital output	PV (Present value)					
		1. Thermocouple, RTD: Temperature detection value [Measuring temperature value × 10 (displaying decimal one point)]					
		2. Voltage, Current Input: 0~8,000					
		Current output			DC 4~20mA		
		Max. resolution			4µA (1/4,000)		
	Transistor output	Absolute max. output			Voltage: 15V, Current: 25mA		
		Max. pulse output			1ms (1/4000: 1ms unit)		
		Output control period			1~100sec (1/1,000)		
		Rated load voltage			DC 24V		
		Load voltage range for usage			DC 20.4~26.4V		
		Max. load current			70mA		
		Max. voltage drop (ON)			DC 1.5V (70mA)		
		Response time	Off → On On → Off		1ms 1ms		
		Common method			2 points/COM		
		Insulation method			Between output terminal and PLC power supply: Photocoupler, Between loops: No insulation		
		Number of loops			2 (Simultaneous 2 loops, including V and transistor output, available to use)		
		Digital input			MV (Manipulated value): Current, Transistor output: 0~4,000		

● PID specifications

Item		Specifications
Setting range of PID values	P	1~10,000 [0.01~100.00 (%)] (Proportion control when I/D values are 0.0)
	I	1~36,000 [0.0~3600.0 (sec)] (Integration control disabled if set 0.0)
	D	1~36,000 [0.0~3600.0 (sec)] (Differentiation control disabled if set 0.0)
SV and PV range		1. Thermocouple, RTD: Temperature detection value [Measuring temperature value × 10 (Displaying decimal one point)] 2. Voltage, Current input: 0~8,000
MV range		0~4,000
MMV range		0~4,000
No. of control loops		2 loops
Control period		200ms
Processing type		Measured-value derivative (pre-derivative) type

● Common specifications

Item		Specifications
External power supply	Voltage range	DC 20.4~26.4V
	Current consumption	90mA
	Internal current consumption	354mA
	Weight	370g

Thermocouple module (GM4/6)

Programmable Logic Controller

■ Features

- 5 thermocouple types available (KS, JIS, ANSI, DIN, BS)
- Automatic reference junction compensation
- Burn-out detection in every channel



■ Specifications

Item	G4F-TC2A		G6F-TC2A ^{*1)}		
Thermocouple	K, J, E, T, B, R, S (Setting per channel available)				
TC input point	4 Channels				
Digital input	Digital conversion value: 0~16,000 Temperature conversion value: (Measuring temperature range of thermocouple) × 10				
Temperature input range	Thermocouple type	DIN specification	BS specification	Measuring temperature range (°C)	Measuring voltage range (µV)
	K	NiCr-Ni	NiCr-NiAl	-200.0~1200.0	-5,891~48,828
	J	-	Fe-CuNi	-200.0~800.0	-7,890~45,498
	E	-	NiCr-CuNi	-150.0~600.0	-7,279~45,085
	T	-	Cu-CuNi	-200.0~400.0	-5,603~20,869
	B	-	PtRh30-PtRh6	400.0~1,800.0	786~13,585
	R	-	PtRh13-Pt	0.0~1,750.0	0~21,006
S	PtRh-Pt	PtRh10-Pt	PtRh10-Pt	0.0~1,750.0	0~18,612
Reference junction compensation	Automatic compensation				
Max. conversion speed	50ms/Channel				
Burn-out detection	Every channel				
Accuracy	± [Full scale × 0.3%+1°C (Reference junction compensation error)]				
Current consumption	450mA		5V/100mA, 15V/40mA, -15V/20mA		

*1) If you use an analog module (G6F-TC2A) in GM6, you are supposed to do GM6-PAFB or GM6-PDFB for its operation.

RTD* module (GM4)



■ Features

- Burn-out detection in every channel

■ Specifications

Item	G4F-RD2A
Connectable RTD	Pt100 (JIS C1640-1989, DIN 43760-1980) JPt100 (KS C1603-1991, JIS C1604-1981)
Input channel	4 Channels
Digital output	Digital conversion value: 0~16,000, Detected temperature conversion value: -2,000~6,000
Temperature input range	Pt100: -200.0~600.0°C (18.48~313.59Ω) JPt100: -200.0~600.0°C (17.14~317.28Ω)
Burn-out detection	Every channel
Max. conversion speed	50ms/Channel (Full scale)
Accuracy	±0.5% (Full scale)
Current consumption	420mA

* RTD: Resistance thermometer device.



PID control module (GM4)

Programmable Logic Controller

■ Features



- PID control: Max. 16 loops
- Forward/Reverse control selectable
- Manually manipulated value output available
- Measured-value derivative type
- LED display for an error and operation condition of each loop
- Autotuning function



■ Specifications

Item	G4F-PIDB	
PID control loops	16	
PID constant	P value (P)	0.01~100.00 (%)
	I value (I)	0.0~3,000.0 (sec)
	D value (D)	0.0~3,000.0 (sec)
Setting range (SV)	0~16,000	
Input range (PV)	0~16,000	
Output range (MV)	0~16,000	
Manually manipulated value	0~16,000	
LED function	Run/Stop	LEDs of corresponding loops ON if they run
	Error	LED flickering
Control action	Forward/Reverse action control available	
Control cycle	0.01~99.99s	
Processing type	Measured-value derivative (Pre-derivative) type	
Internal current consumption (DC 5V)	600mA	
Output point/COM	16 points/COM	

■ PID control operation



Analog timer module (GM4)

■ Features

- Setting and adjusting time (Highly precise range) available
- Max. 8 points of Analog Timer per module applicable
- Various range of setting time (0.1~600sec)
- Easy timer setting with switch manipulation
- LED display for timer operation status
- Timer setting available in run mode



■ Specifications

Item	G4F-AT3A	
Point	8 points	
Timer setting value range (sec)	0.1~1.0, 1~10, 10~60, 60~600	Setting can be done for each point
Setting method		Set the operation mode selection SW to TEST side
Backup method	Setting by adjustment volume	
Accuracy	$\pm 2.0\%$ (Full-scale)	
LED function	Operation LED	8 points
	Contact LED	8 points
Operation	CR analog type (On-delay) operation	
Internal current consumption (DC 5V)	200mA	

Positioning module (APM): (GM4/6)

Programmable Logic Controller

■ Features

- Highly reliable position control with LSIS ASIC-embedded processor
- Enhanced control with fast control processing speed
- High-speed motor control (Max. pulse output: 1Mbps)
- Arc/linear interpolation, separate/synchronous operation
- Trapezoidal & S-curve acceleration/deceleration function
- Easy and quick to control through external input (JOG operation included)
- Encoder input support
- Self-diagnosis, monitoring and test by APM
 - Diagnosis for I/O signal line
 - Easy to set position control parameters
 - Monitoring/tracking/simulation
 - Information and solution for each error provided
 - Available to edit operation parameter data in EXCEL



■ Specifications

Item		Open collector type			Line drive type											
Number of axes	1	2	3	1	2	3										
	GM4	G4F-PP1O	G4F-PP2O	G4F-PP3O	G4F-PP1D	G4F-PP2D	G4F-PP3D									
CPU type	GM6	G6F-PP1O	G6F-PP2O	G6F-PP3O	G6F-PP1D	G6F-PP2D	G6F-PP3D									
Output signal		Pulse														
Interpolation		2- and 3-axis linear interpolation/2-axis arc interpolation														
Speed (Position) control		Yes														
Positioning data		400(axis)														
Setting unit		mm, inch, degree, pulse														
Data backup		Flash memory														
Position address range		-2,147,483,648~2,147,483,647 0.01~20,000,000.00 (mm/min) 0.001~2,000,000.00 (inch/min) 0.001~2,000,000.00 (degree/min)														
Positioning speed range ^{*1)}		1~200,000 (pulse/s)			1~1,000,000 (pulse/s)											
Max. output pulse		200kbps			1Mbps											
Output frequency/distance		200kbps/2m			1Mbps/10m											
Acceleration/		Trapezoidal & S-curve acceleration/deceleration														
Deceleration pattern and time		1~65,535ms														
Origin point return method		Approximate origin point (DOG (ON)/HOME, DOG (OFF)/HOME, DOG), Upper/Lower limit														
High-speed return to origin		Yes (Floating point)														
Manual operation		JOG MPG ^{*2)} /Inching operation														
M code		1~65,535														
Synchronous operation		Yes														
Backlash compensation		Yes														
Others	Speed change during operation															
	Position address change during operation															
	Speed/position switching															
	Zone output ^{*2)} : 3 ranges settings available (GM4 only)															
Simultaneous operation																
Current consumption (DC 5V)		730mA	760mA	770mA	700mA	720mA	740mA									
		480mA	490mA	500mA	630mA	750mA	840mA									



*1) In case of mm, inch or degree, speed limit varies according to pulse per rotation, transfer distance per rotation and unit multiplier.

*2) Available at GM4. MPG operation and zone output are not available at GM6.

I/O interface with external equipment

Programmable Logic Controller

■ Pin layout for (G4F-PP□O, G4F-PP□D)

Pin layout	For	Pin number			Signal name	Signal direction APM - Ext. device	Condition	
		X	Y	Z				
 1 axis	A x i s	21	41	61	FP+	Pulse output (Differential +)	→	
		22	42	62	FP-	Pulse output (Differential -)	→	
		23	43	63	RP+	Pulse sign (Differential +)	→	
		24	44	64	RP-	Pulse sign (Differential -)	→	
		25	45	65	OV+ *	High limit	←	
		26	46	66	OV- *	Low limit	←	
		27	47	67	STOP	External stop signal	←	
		28	48	68	DOG	Approximate origin	←	
		29	49	69	VTP	Speed/Position switching signal	←	
		30	50	70	ECMD	External command signal	Start	
						Skip	↓↑	
						JOG+(Forward)	↓↑	
		31	51	71	JOG-	JOG reverse operation	←	
		32	52	72	COM	Common (OV+, OV-, STOP, DOG, VTP, ECMD, JOG-)	↔	
		33	53	73	DRVIN *	Drive unit ready signal	←	
		34	54	74	DRVIN COM	Drive unit ready signal common	↔	
		35	55	75	HOME +24V	Zero signal (+24V)	←	
		36	56	76	NC	Not used		
		37	57	77	HOME +5V	Zero signal (+5V)	←	
		38	58	78	HOME COM	Zero signal (+24V, +5V) Common	↔	
		39	59	79	NC	Not used		
		40	60	80	NC	Not used		
 2/3 axes	C o m m o n	1			MPG A+	Manual pulse generator/Encoder A+ Input	←	
		2			MPG A-	Manual pulse generator/Encoder A- Input	←	
		3			MPG B+	Manual pulse generator/Encoder B+ Input	←	
		4			MPG B-	Manual pulse generator/Encoder B- Input	←	
		5			MPG Z+	Encoder Z+ Input	←	
		6			MPG Z-	Encoder Z- Input	←	
		7			CON	External simultaneous start	←	
		8			EMG *	Emergency stop	←	
		9			NC	Not used		
		10			COM	(CON, EMG) Common	↔	
		11			Out 1	Transistor output of Zone 1	→	
		12			Out 2	Transistor output of Zone 2	→	
		13			Out 3	Transistor output of Zone 3	→	
		14			COM	ZONE Common	↔	
		15, 16, 17, 18, 19, 20			NC	Not used		

* High/low limit, drive unit ready signal, emergency stop signal should be connected to DC 24V.

■ Pin layout for (G6F-PP□O, G6F-PP□D)

Pin layout	For	Pin number			Signal name	Signal direction APM - Ext. device	Condition	
		X	Y	Z				
1 axis	A x i s	21A	1B	21B	FP+	Pulse output (Differential +)	→	
		22A	2B	22B	FP-	Pulse output (Differential -)	→	
		23A	3B	23B	RP+	Pulse sign (Differential +)	→	
		24A	4B	24B	RP-	Pulse sign (Differential -)	→	
		25A	5B	25B	OV+ *	High limit	←	↓
		26A	6B	26B	OV- *	Low limit	←	↓
		27A	7B	27B	STOP	External stop signal	←	↑
		28A	8B	28B	DOG	Approximate origin	←	↑
		29A	9B	29B	VTP	Speed/Position switching signal	←	↑
		30A	10B	30B	ECMD	External command signal	Start Skip JOG+(Forward)	↑
		31A	11B	31B	JOG-	JOG reverse operation	←	↓
		32A	12B	32B	COM	Common (OV+, OV-, STOP, DOG, VTP, ECMD, JOG-)	↔	
		33A	13B	33B	DRVIN *	Drive unit ready signal	←	↓
		34A	14B	34B	DRVIN COM	Drive unit ready signal common	↔	
		35A	15B	35B	HOME +24V	Zero signal (+24V)	←	↑
		36A	16B	36B	HOME COM	Zero signal (+24V, +5V) Common	↔	
		37A	17B	37B	HOME +5V	Zero signal (+5V)	←	↑
		38A	18B	38B	P COM	External 5V, 24V GND (Not used in case of line drive output)	↔	
		39A	19B	39B	5V	External 5V Power input (Not used in case of line drive output)	←	
		40A	20B	40B	24V	External 24V Power input (Not used in case of line drive output)	←	
2/3 axes	C o m m o 	1A		MPG A+	Manual pulse generator/Encoder A+ Input	←		
		2A		MPG A-	Manual pulse generator/Encoder A- Input	←		
		3A		MPG B+	Manual pulse generator/Encoder B+ Input	←		
		4A		MPG B-	Manual pulse generator/Encoder B- Input	←		
		5A		NC	Not used			
		6A		NC	Not used			
		7A		CON	External simultaneous start	←	↑	
		8A		EMG *	Emergency stop	←	↓	
		9A		NC	No use			
		10A		COM	(CON, EMG) Common	↔		
		11A, 12A, 13A, 14A, 15A, 16A, 17A, 18A, 19A, 20A		NC	Not used			


* High/low limit, drive unit ready signal, emergency stop signal should be connected to DC 24V.

Example of connection with drivers

Programmable Logic Controller


■ MR-J2/J2S-□A connection (line drive)

G4F-PP1/2/3D




■ FDA-5000 AC Servo driver connection (open collector)

G4F-PP1/2/3O




■ MR-J2/J2S-□A connection (line drive)

G6F-PP1/2/3D



■ FDA-5000 AC Servo driver connection (line drive)

G4F-PP1/2/3D



* Pin layout in G4F-PP□D(O) and G6F-PP□D(O) is different.

High speed counter module (GM4/6)

Programmable Logic Controller

■ Features

- Pulse input support (5V, 12V, 24V)
- Counting range from -2,147,483,648 to 2,147,483,647
- Max. counting speed: 500kpps
- Coincidence output selection (Max. 4 points)
- Various multiplication (1/2/4-multiplication phase up/down counter)
- Phase input (A, B and Z phase)
- External preset input
(G4F-HO1A, G4F-HD1A, G6F-HO1A, G6F-HD1A, G6F-HSCA)
- Incremental encoder available to use
(Absolute encoder: Not available)



■ Specifications

		Item	New type			G6F-HSCA	
			G4F-HSCA	G4F-HO1C	G4F-HD1C		
Number of channel(s)		1	2		1		
Counter	Phase	A, B, Z (phase)	A, B (phase)		A, B, Z (phase)		
input	Level	DC 5V, 12V, 24V	EIA RS-422A standard (DC5V)		DC 5V, 12V, 24V		
signal	Type	Voltage input			DC 5V, 12V, 24V		
Counting range		0~16,777,215	-2,147,483,648~-2,147,483,647	0~16,777,215	(Binary 24bits)		
Counting speed		50kpps	200kpps	500kpps	50kpps		
Up/down counter	1-phase input	Program or B phase			-		
setting	2-phase input	Phase difference			-		
Multiplication	1-phase input	-	A-phase: Up count, B-phase: Down count	-		-	
	2-phase input	1/2/4 multiplication (DIP S/W)	1/2 multiplication (Program)	1/2/4 multiplication (Program)	1/2/4 multiplication (DIP S/W)		
External input	Preset	-	DC 5V, 12V, 24V	DC 24V		DC 24V	
	Limit switch	DC 24V	-	DC 24V		DC 24V	
	Gate	-	DC 5V, 12V, 24V	-		-	
External output	Type	OUT1, OUT2 (Select: >, =, <)	OUT1, OUT2 (Select: >, =, <, section)	OUT1, OUT2 (Select: >, =, <)		OUT1, OUT2 (Select: >, =, <)	
	Signal	Tr. output DC 24V, 200mA	Tr. output DC 24V	Tr. output DC 24V, 200mA		Tr. output DC 24V, 200mA	
Additional functions		Count clear, Count latch, Sampling count, Pulse frequency count, Periodic pulse count			-		
Current consumption		250mA	270mA	330mA	180mA		

GMWIN software

Programmable Logic Controller

■ Features

- Supports the international language (IEC61131-3)
 - IL, LD, SFC
- Supports Windows 95, 98, ME, NT, 2000, XP
- Simulation
 - Program test and debugging without PLC
- Editing, monitoring, debugging using symbol and variable name
- Automatic memory allocation support
 - Compiler sets a variable location automatically
- Optimization (PLC code) by compiler method
- User-defined function/function block support

■ Features

- Function (Type conversion, Arithmetic, Comparison, Array operation function)
- Function block (Timer, Counter, etc)


■ System requirement

- Intel compatible PC (Intel Pentium CPU or later)
- Windows 95, 98, ME, NT, 2000, XP
- Video adapter (VGA or later)
- Mouse/Printer compatible with Windows
- 128M RAM and 20M free hard disk space


■ Languages

- IL (Instruction list)
- LD (Ladder diagram)
- SFC (Sequential function chart)

■ Cable connection for PC: K1C-050A



■ System configuration



XGT Panel XP Series

Programmable Logic Controller

■ Features

- High and vivid distinction with 65,536 colors
- Various vector symbols and high quality raster symbols
- Support diverse file types including BMP, JPG, GIF, and WMF, etc
- Simple movie clip effects with GIF animation
- 10/100 BASE-T Ethernet interface
- Convenient and easy screen editing
- Strengthened data management (Logging, Recipe, and Alarm)
- Read function of a controller's state information (Monitoring and maintenance)
- Multi-lingual display up to 4 languages and easy switching
- Offline program simulation
- Tag function of the HMI S/W (Easy to change the address of the graphic objects)
- USB host for the use of peripheral devices (Mouse, keyboard, printer, etc)
- Sufficient memory space for screen saving (10MB)



■ Specifications

Item	XP30-BTE/DC	XP30-BTA/DC	XP30-TTA/DC	XP50-TTA/DC	XP70-TTA/AC XP70-TTA/DC	XP80-TTA/AC XP80-TTA/DC	XP90-TTA/AC					
	Mono		Color									
Display description	Mono Blue LCD						TFT Color LCD					
Display Size (inch)	14cm (5.7")		21cm (8.4")	26cm (10.4")	31cm (12.1")	38cm (15")						
Resolution	320×240		640×480		800×600	1024×768						
Color	8-bit Gray Scale		320×240									
Backlight	LED		CCFL (whole LCD), auto On/Off (50,000hr)									
Contrast	Adjustable		CCFL (whole LCD), auto On/Off (50,000hr)									
Luminance	230cd/m ²		400cd/m ²	480cd/m ²	430cd/m ²	400cd/m ²	450cd/m ²					
Viewing angle	Up/Down(Degree)	20/40	70/50	60/50	65/45	75/45	60/50					
	Left/Right(Degree)	45/45	70/70	65/65	65/65	65/65	75/75					
Touch panel	4-wire system, analog		8-wire system, analog									
LED	Green: Run (Monitoring, download drawing data) Red: Error (Communication error, drawing data error)											
Processor	ARM920T(32bit RISC), 200MHz											
Memory	Display data	3MB	10MB				20MB					
	Backup data	128KB	512KB (Logging, alarm data saving)									
Ethernet	-		1ch, IEEE802.3, 10/100Base-T									
USB interface	USB Host×1		USB Host×2									
Serial	RS-232C	2ch (1 port for PC communication)										
	RS-422/485	1ch, 422/485										
CF memory card interface	-		CF memory card (TYPE-1) ×1									
AUX interface	-		Optional									
Certification	CE, UL, KCC											
Protection	IP65F (Front Water Proof Structure)											
Size (W×H×D)mm	181×140×56.5	181×140×66.5	240×174×73	317×243×73	395×294×73							
Panel Cut (W×H)mm	155.5×123		228×158	294×227	383×282							
Weight (kg)	0.62	0.75	1.4	2.2	2.4	3.9						
	Rated voltage		DC 24V									
Power	Permitted voltage	AC	-									
	DC	MIN 19.2 VDC, MAX 28.8 VDC										
	Watt	AC	-	-	-	37	40					
	DC	5	8.5	20	27	30	46					

XGT PANEL

Programmable Logic Controller

■ Features

Enhancing User-friendliness

- Flexible to draw: 192 X 64 Dot Graphic LCD
- Easy to upgrade: O/S and font download
- Various tag/drawing functions support: 15 types
- Easy to manage data: internal memory (1000 words) support
- User-defined function keys support for each screen (F1~F4, ▲, ▼, ▶, ▷)
- User-defined bitmap file input support
- Region-based upload/download support
- Built-in RTC: B type
- Large screen memory: 256K

Flexible to supply power

- 5V supply by loader port for LS PLC and INV connection
- DC 24V supply from DC 24V input terminal

Language support

- English, Chinese, Korean
- Font-download adoption support



Strong communication functions

- Separate 2Ch support: RS-232C and RS-422/485
- Multi master communication (N:M) support
 - Monitoring M PLCs with N XGT PANELs

Various communication modes and protocol driver supply


- LS PLC: loader and link (Cnet)
- LS VFD: loader (iS5/IP5(A)/iV5) and RS-485
- MODBUS ASCII/RTU protocol
- Mitsubishi FX series
- OMRON C-mode protocol
- Communication drivers are continually added and updated.

■ Performance Specifications


Item		Specifications		Remark
		XP10BKA/DC	XP10BKB/DC	
Input power		4.9~5.1VDC (RS-232C Connector), or 21.6V~26.4VDC (Power supply connector)		
Display		LED Back-light (192*64 Dot)		
Communication Interface		RS-232C, RS-422/485		Independent 2 channels
Memory		256k bytes		
Languages		English, Chinese, Korean		
RTC		None	Supports	
Up/Download spec.		Speed: 115,200bps Each memory area can be up/downloaded in part		
Key		12keys (F1~F4, ESC, ALM, ▲, ▼, ▶, ▷, SET, ENT)		
System memory	User area	M000~M899 (900 Word)	Latch area is supported, in XP 10BKB/DC	
	System flags	M900~M999 (100 Word)		

■ Easy drawing tool: Panel editor


- Easy Programming
- Drawing Tool
- Direct Device Input
- Snap/Align Functions
- Print Function
- Simple Memory Management



■ Cable connection for program downloading



■ Dimensions



Command

Programmable Logic Controller

■ Sequence operation

Symbol	Description	Remark
— —	Normally open contact	
— / —	Normally closed contact	
— P —	Positive transition-sensing contact	
— N —	Negative transition-sensing contact	
()	Coil	
(/)	Negative coil	
()	Set (Latch) coil	
(R)	Reset (Unlatch) coil	
(P)	Positive transition-sensing coil	
(N)	Negative transition-sensing coil	
→>	Jump to label	
— RET —	End subroutine program	
— SC —	Call subroutine	

■ Function





Instruction	Symbol	Description	Remark
MOVE		Data movement IN1: Value to be moved (ANY) OUT: Moved value (ANY)	
**** _TO_ ****		Type conversion IN: Input OUT: Output Type conversion function SINT_TO_INT plus 14 types INT_TO_SINT plus 14 types DINT_TO_SINT plus 14 types LINT_TO_SINT plus 14 types USINT_TO_SINT plus 14 types UINT_TO_SINT plus 15 types UDINT_TO_SINT plus 16 types ULINT_TO_SINT plus 14 types BOOL_TO_SINT plus 12 types BYTE_TO_SINT plus 13 types WORD_TO_SINT plus 13 types DWORD_TO_SINT plus 15 types LWORD_TO_SINT plus 14 types BCD_TO_SINT plus 8 types REAL_TO_SINT plus 9 types LREAL_TO_SINT plus 9 types STRING_TO_SINT plus 18 types NUM_TO_STRING TIME_TO_UDINT plus 2 types DATE_TO_UINT plus 2 types TOD_TO_UDINT plus 2 types DT_TO_DATE plus 3 types"/>	LINT, ULINT LWORD, REAL, LREAL are available in GM4C *
TRUNC		Converting Real to Integer number IN: Input (REAL, LREAL) OUT: Output (DINT, LINT)	GM4C only
ADD		Addition IN1: Value to be added IN2~IN8: Value to add (ANY_NUM) OUT: Added value (ANY_NUM)	
SUB		Subtraction IN1: Value to be subtracted (ANY_NUM) IN2: Value to subtract (ANY_NUM)	
MUL		Multiplication IN1: Multiplicand IN2~IN8: Multiplier (ANY_NUM) OUT: Multiplied value (ANY_NUM)	
DIV		Division IN1: Dividend (ANY_NUM) IN2: Divisor (ANY_NUM) OUT: Quotient (ANY_NUM)	

* GM4C: GM4-CPUC

Command

Programmable Logic Controller

■ Function

Instruction	Symbol	Description	Remark
MOD		Divided result (Remainder) IN1: Dividend (ANY_INT) IN2: Divisor (ANY_INT) OUT: Remainder (ANY_INT)	
EXPT		Exponential operation IN1: Real number (ANY_REAL) IN2: Exponent (ANY_NUM) OUT: Result (ANY_REAL)	GM4C only
ABS		Absolute value operation IN: Input (ANY_NUM) OUT: Absolute value (ANY_NUM)	GM4C only
SQRT		Square root operation IN: Input value (ANY_REAL) OUT: Square root value (ANY_REAL)	GM4C only
LN		Natural logarithm operation IN: Input value (ANY_REAL) OUT: Natural logarithm value (ANY_REAL)	GM4C only
LOG		Base 10 logarithm operation IN: Input value (ANY_REAL) OUT: Base 10 logarithm value (ANY_REAL)	GM4C only
EXP		Natural exponential operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
SIN		Sine operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
COS		Cosine operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
TAN		Tangent operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
ASIN		Arc Sine operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
ACOS		Arc Cosine operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
ATAN		Arc Tangent operation IN: Input value (ANY_REAL) OUT: Result (ANY_REAL)	GM4C only
SHL		Shift left operation IN: Bit string (ANY_BIT) N: Bit number to be shifted (INT) OUT: Shifted value (ANY_BIT)	
SHR		Shift right operation IN: Bit string (ANY_BIT) N: Bit number to be shifted (INT) OUT: Shifted value (ANY_BIT)	
ROL		Rotate to left IN: Value to be rotated (ANY_BIT) N: Bit number to rotate (INT) OUT: Rotated value (ANY_BIT)	
ROR		Rotate to right IN: Value to be rotated (ANY_BIT) N: Bit number to rotate (INT) OUT: Rotated value (ANY_BIT)	

■ Function

Instruction	Symbol	Description	Remark
AND		Logical AND IN1~IN8: Input (ANY_BIT) OUT: AND Result (ANY_BIT)	
OR		Logical OR IN1, IN2: Input (ANY_BIT) OUT: OR Result (ANY_BIT)	
XOR		Exclusive OR IN1, IN2: Input (ANY_BIT) OUT: XOR Result (ANY_BIT)	
NOT		Logic inversion (NOT) IN: Input (ANY_BIT) OUT: NOT Result (ANY_BIT)	
SEL		Selection G: Selection IN0, IN1: Value to be selected (ANY) OUT: Selected value (ANY)	
MAX		Maximum value IN1: Value to be compared (ANY) IN2~IN8: Value to compare (ANY) OUT: Maximum value (ANY)	
MIN		Minimum value IN1: Value to be compared (ANY) IN2~IN8: Value to compare (ANY) OUT: Minimum value (ANY)	
LIMIT		Limit upper and lower boundary MN: Minimum value (ANY) IN: Value to be limited (ANY) MX: Maximum value (ANY) OUT: Value in the range (ANY)	
MUX		Multiplexer K: Selection (INT) IN0~IN6: Value to be selected (ANY) OUT: Selected value (ANY)	
GT (>)		'Greater than' comparison IN1: Value to be compared (ANY) IN2~IN8: Comparing value (ANY) OUT: Comparison result (BOOL) If IN1 > IN2 > ... IN7 > IN8, output is 1	
GE (>=)		'Greater than or equal to' comparison IN1: Value to be compared (ANY) IN2~IN8: Comparing value (ANY) OUT: Comparison result (BOOL) If IN1 ≥ IN2 ≥ ... IN7 ≥ IN8, output is 1	
EQ (=)		'Equal to' comparison IN1: Value to be compared (ANY) IN2~IN8: Comparing value (ANY) OUT: Comparison result (BOOL) If IN1 = IN2 = ... IN7 = IN8, output is 1	
LE (<=)		'Less than or equal to' comparison IN1: Value to be compared (ANY) IN2~IN8: Comparing value (ANY) OUT: Comparison result (BOOL) If IN1 ≤ IN2 ≤ ... IN7 ≤ IN8, output is 1	
LT (<)		'Less than' comparison IN1: Value to be compared (ANY) IN2~IN8: Comparing value (ANY) OUT: Comparison result (BOOL) If IN1 < IN2 < ... IN7 < IN8, output is 1	
NE (≠)		'Not equal to' comparison IN1, IN2: Comparing value (ANY) OUT: Comparison result (BOOL) If IN1 ≠ IN2, output is 1	

Command

Programmable Logic Controller

■ Function

Instruction	Symbol	Description	Remark
LEN		Character string length IN: Character string Input (STRING) OUT: Character string length (INT)	
LEFT		Left part of a character string IN: Input character string (STRING) L: Character string length to output (INT) OUT: Output character string (STRING)	
RIGHT		Right part of a character string IN: Input character string (STRING) L: Character string length to output (INT) OUT: Output character string (STRING)	
MID		Middle part of a character string IN: Input character string (STRING) L: Character string length to output (INT) P: String location of character string (INT) OUT: Output character string (STRING)	
CONCAT		Concatenation of a character string IN1~IN8: Input character string (STRING) OUT: Output character string (STRING)	
INSERT		Insertion of s character string IN1: Character string to be inserted (STRING) IN2: Character string to insert (STRING) P: Position to insert a character string (INT) OUT: Output character string (STRING)	
DELETE		Deletion of a character string IN: Input character string (STRING) L: Length of a character string to be deleted (INT) P: Position of a character string to delete (INT) OUT: Output character string (STRING)	
REPLACE		Character string Replacement IN1: Character string to be replaced (STRING) IN2: Character string to replace (STRING) L: Length of character string to be replaced (INT) P: Position of character string to be replaced (INT) OUT: Character string output (STRING)	
FIND		Find a character string IN1: Input character string (STRING) IN2: Character string to find (STRING) OUT: Location of character string to be found (INT)	
ADD_TIME		Time addition IN1: Reference time (TIME, TOD, TD) IN2: Time to add (TIME) OUT: Added result of TOD or time (TIME, TOD, TD)	
SUB_TIME		Time subtraction IN1: Reference time (TIME, TOD, TD) IN2: Time to subtract (TIME) OUT: Subtracted result of TOD or time (TIME, TOD, TD)	
SUB_DATE		Date and time subtraction IN1: Reference Date (DATE) IN2: Date to be subtracted (DATE) OUT: The difference between two dates as time (TIME)	
SUB_TOD		TOD subtraction IN1: Reference TOD (TIME_OF_DAY) IN2: TOD to subtract (TIME_OF_DAY) OUT: Subtracted result time (TIME)	










■ Function

Instruction	Symbol	Description	Remark
SUB_DT		Date and time subtraction IN1: Reference DATE_AND_TIME (DATE_AND_TIME) IN2: DATE_AND_TIME to be Subtracted (DATE_AND_TIME) OUT: Subtracted result time (TIME)	
MUL_TIME		Time multiplication IN1: Time to be multiplied (TIME) IN2: Multiplying value (ANY_NUM) OUT: Multiplied result (TIME)	
DIV_TIME		Time division IN1: Time to divide (TIME) IN2: Value to divide (ANY_NUM) OUT: Divided result time (TIME)	
CONCAT_TIME		Character string concatenation IN1: Date input (DATE) IN2: TOD input (TOD) OUT: DT output	
DI		Not to permit task program operation REQ: Requires to invalidate task program (BOOL) OUT: If DI is executed, it will be 1 (BOOL)	
EI		To permit running for task program REQ: Requires to permit running task program (BOOL) OUT: If EI is executed, it will be 1 (BOOL)	
STOP		Stop by program REQ: STOP Request (BOOL) OUT: If STOP is executed, it will be 1 (BOOL)	
ESTOP		Emergency stop by program REQ: Emergency stop request (BOOL) OUT: If ESTOP is executed, it will be 1 (BOOL)	
DIREC_IN		Instant refreshment of input data BASE: Base number of input module (USINT) SLOT: Slot number of input module (USINT) MASK_L: Designating bits not to be refreshed among lower 32-bit data of input (DWORD) MASK_H: Designating bits not to be refreshed among upper 32-bit data of input (DWORD) OUT: If refreshment is completed, it will be 1 (BOOL)	
DIREC_O		Instant Refreshment of output data BASE: Base number of output module (USINT) SLOT: Slot number of output module (USINT) MASK_L: Designating bits not to be refreshed among lower 32-bit data of output (DWORD) MASK_H: Designating bits not to be refreshed among upper 32-bit data of output (DWORD) OUT: If refreshment is completed, it will be 1 (BOOL)	
WDT_RST		Watchdog timer reset REQ: Watchdog timer initialization request (BOOL) OUT: If WDT_RST is executed, it will be 1 (BOOL)	
MCS		Master control NUM: Nesting number (INT) OUT: Dummy (Always 0)	
MCSCLR		Master control clear NUM: Nesting number (INT) OUT: If MCSCLR is executed, it will be 1 (BOOL)	

Command

Programmable Logic Controller

■ Function block

Instruction	Symbol	Description	Remark
TON		On delay timer EN: Timer operation condition (BOOL) PT: Preset time (TIME) Q: Timer output (BOOL) ET: Elapsed time (TIME)	
TOF		Off delay timer EN: Timer operation condition (BOOL) PT: Preset time (TIME) Q: Timer output (BOOL) ET: Elapsed time (TIME)	
TP		Pulse timer EN: Timer operation condition (BOOL) PT: Preset time (TIME) Q: Timer output (BOOL) ET: Elapsed time (TIME)	
CTU		Up counter CU: Up counter pulse input (BOOL) R: Reset input (BOOL) PV: Preset value (INT) Q: Up counter output (BOOL) CV: Current value (INT)	
CTD		Down counter CD: Down counter pulse input (BOOL) LD: Load preset value (BOOL) PV: Preset value (INT) Q: Down counter output (BOOL) CV: Current value (INT)	
CTUD		Up/Down counter CU: Up counter pulse input (BOOL) CD: Down counter pulse input (BOOL) R: Reset input (BOOL) LD: Load preset value (BOOL) PV: Preset value (INT) QU: Up counter output (BOOL) QD: Down counter output (BOOL) CV: Current value (INT)	
SEMA		Semaphore for system resource allocation CLAIM: Resource monopoly request signal (BOOL) RELEASE: Release signal (BOOL) BUSY: Waiting signal not to obtain the claimed resource (BOOL)	
SR		Set priority bistable S1: Set condition (BOOL) R: Reset condition (BOOL) Q1: Operation result (BOOL)	
RS		Reset priority bistable S: Set condition (BOOL) R1: Reset condition (BOOL) Q1: Operation result (BOOL)	
R_TRIGGER		Rising edge detection CLK: Input clock (BOOL) Q: Rising edge detection result (BOOL)	
F_TRIGGER		Falling edge detection CLK: Input signal (BOOL) Q: Falling edge detection result (BOOL)	
RTC_SET		RTC data setting REQ: Request (BOOL) DATA: Time data to input (ARRAY) DONE: Without an error, it will be 1 (BOOL) STAT: If an error occurs, an error code appears (USINT)	

Product list

Programmable Logic Controller

■ GM7/GM7U

Type	Part Number	Specification	Power supply	Remarks
GM7 main	G7M-DR10A (/DC)	DC 24V Input 6 points, Relay output 4 points	AC 100~240V (DC 24V)	
	G7M-DR20A (/DC)	DC 24V Input 12 points, Relay output 8 points		
	G7M-DR30A (/DC)	DC 24V Input 18 points, Relay output 12 points		
	G7M-DR40A (/DC)	DC 24V Input 24 points, Relay output 16 points		
	G7M-DR60A (/DC)	DC 24V Input 36 points, Relay output 24 points		
	G7M-DT10A	DC 24V Input 6 points, Tr. output 4 points	AC 100~ 240V	
	G7M-DT20A	DC 24V Input 12 points, Tr. output 8 points		
	G7M-DT30A	DC 24V Input 18 points, Tr. output 12 points		
	G7M-DT40A	DC 24V Input 24 points, Tr. output 16 points		
	G7M-DT60A	DC 24V Input 36 points, Tr. output 24 points		
GM7U main	G7M-DR20U (/DC)	DC 24V Input 12 points, Relay output 8 points	AC 100~ 240V (DC 24V)	
	G7M-DR30U (/DC)	DC 24V Input 18 points, Relay output 12 points		
	G7M-DR40U (/DC)	DC 24V Input 24 points, Relay output 16 points		
	G7M-DR60U (/DC)	DC 24V Input 36 points, Relay output 24 points		
	G7M-DRT20U (/DC)	DC 24V Input 12 points, Tr. output 4 points/Relay output 4 points		
	G7M-DRT30U (/DC)	DC 24V Input 18 points, Tr. output 4 points/Relay output 8 points		
	G7M-DRT40U (/DC)	DC 24V Input 24 points, Tr. output 4 points/Relay output 12 points		
	G7M-DRT60U (/DC)	DC 24V Input 36 points, Tr. output 4 points/Relay output 20 points		
	G7M-DT20U (N) (/DC)	DC 24V Input 12 points, NPN Tr. output 8 points		
	G7M-DT30U (N) (/DC)	DC 24V Input 18 points, NPN Tr. output 12 points		
	G7M-DT40U (N) (/DC)	DC 24V Input 24 points, NPN Tr. output 16 points		
	G7M-DT60U (N) (/DC)	DC 24V Input 36 points, NPN Tr. output 24 points		
	G7M-DT20U (P) (/DC)	DC 24V Input 12 points, PNP Tr. output 8 points		
	G7M-DT30U (P) (/DC)	DC 24V Input 18 points, PNP Tr. output 12 points		
	G7M-DT40U (P) (/DC)	DC 24V Input 24 points, PNP Tr. output 16 points		
	G7M-DT60U (P) (/DC)	DC 24V Input 36 points, PNP Tr. output 24 points		
Expansion module	Digital I/O	G7E-DR08A	DC 24V Input 4 points, Relay output 4 points	GM7
		G7E-DR10A	DC 24V Input 6 points, Relay output 4 points	
		G7E-DR20A	DC 24V Input 12 points, Relay output 8 points	
	Input	G7E-DC08A	DC 24V Input 8 points	
		G7E-RY08A	Relay output 8 points	
	Output	G7E-RY16A	Relay output 16 point	
		G7E-TR10A	Tr. output 10 points	
Special module	Analog I/O	G7F-ADHA	Analog input 2Chs, Analog output 1Ch	GM7
		G7F-ADHB	Analog input 2Chs, Analog output 2Chs	
		G7F-ADHC	Analog input 2Chs, Analog output 1Ch	
	Analog Input	G7F-AD2A	Analog input 4Chs	
		G7F-AD2B	Analog input 4Chs	
	Analog Output	G7F-DA2I	Analog current output 4Chs	GM7
		G7F-DA2V	Analog voltage output 4Chs	
	RTD Input	G7F-RD2A	RTD input 4Chs	
	Analog Timer	G7F-AT2A	Analog timer 4Chs	
Comm. module	Cnet I/F	G7L-CUEB	RS-232C 1Ch	GM7
		G7L-CUEC	RS-422 1Ch	
	Fnet I/F	G7L-FUEA	Fnet (dedicated protocol) I/F master	
	Rnet I/F	G7L-RUEA	Rnet (dedicated protocol for SMART I/Os) I/F master	
	Pnet I/F	G7L-PBEA	Profibus-DP slave unit	
	Dnet I/F	G7L-DBEA	DeviceNet slave unit	
Option	RTC pack	G7E-RTCA	RTC unit	GM7 only
	Memory pack	G7M-M256	Memory pack for GM7	
		G7M-M256B	Memory pack for GM7U	

* If a part number ends with /DC, the supply power is DC24V.

* Slim type: G7E-DC08A, G7E-DR08A, G7E-RY8A, G7F-ADHB, G7F-AD2B, G7F-RD2A

Product list

Programmable Logic Controller

■ GM6

Type	Part Number	Specification	Remarks
CPU	GM6-CPUA	Max. I/O: 384 points, Program memory: 68K, Built-in function: RS-232	
	GM6-CPUB	Max. I/O: 384 points, Program memory: 68K, Built-in function: RS-422, PID, RTC	
	GM6-CPUC	Max. I/O: 384 points, Program memory: 68K, Built-in function: RS-232C, PID, RTC, HSC (50kpps)	
Power module	GM6-PAFA	AC input (Free), output: DC 5V 2A, DC 24V 0.3A	
	GM6-PAFB	AC input (Free), output: DC 5V 2A, DC 15V 0.5A, DC -15V 0.2A, when analog module used	Analog
	GM6-PAFC	AC input (Free), output: DC 5V 3.5A, DC 24V 0.3A for 12-slot base board	
	GM6-PA2A	AC 220V Only, output: DC 5V 6A	
	GM6-PDFA	DC 12/24V input, output: DC 5V 2A	
Base	GM6-PDFB	DC 12/24V input, output: DC 5V 3A, DC 15V 0.5A, DC -15V 0.2A, when analog module used	Analog
	GM6-B04M	4-slot base board	
	GM6-B06M	6-slot base board	
	GM6-B08M	8-slot base board	
	GM6-B12M	12-slot base board, Comm I/F module installation: slot 0~7	Not expansible
DC input module	G6I-D21A	DC 12/24V input 8 points, Current Sink/Source type	
	G6I-D22A	DC 12/24V input 16 points, Current Sink/Source type	
	G6I-D22B	DC 24V input 16 points, Current Source type	
	G6I-D24A	DC 12/24V input 32 points, Current Sink/Source type	
	G6I-D24B	DC 24V input 32 points, Current Source type	
AC input module	G6I-A11A	AC 110V input 8 points	
	G6I-A21A	AC 220V input 8 points	
Relay output module	G6Q-RY1A	Relay output 8 points, DC 12/24V, AC 220V, 2A	
	G6Q-RY2A	Relay output 16 points, DC 12/24V, AC 220V, 2A	
	G6Q-RY2B	Relay output 16 points, DC 12/24V, AC 220V, 2A, Surge absorber	AC, DC
Transistor output module	G6Q-TR2A	Tr. (NPN) output 16 points, DC 12/24V, 0.5A	
	G6Q-TR2B	Tr. (PNP) output 16 points, DC 12/24V, 0.5A	
	G6Q-TR4A	Tr. (NPN) output 32 points, DC 12/24V, 0.1A	
	G6Q-TR4B	Tr. (PNP) output 32 points, DC 12/24V, 0.1A	DC
Triac output module	G6Q-SS1A	DC 12/24V input 8 points, AC 100~240V, 0.6A	AC
I/O hybrid module	G6H-DR2A	DC 12/24V input 8 points, Relay output 8 points	
Special module	A/D module	G6F-AD2A	V/I input: 4 CHs, DC 1~5V, 0~10V, -10~10V, 4~20mA
	D/A module	G6F-DA2V	V output: 4 CHs, DC -10~10V
		G6F-DA2I	I output: 4 CHs, DC 4~20mA
HSC module		G6F-HSCA	1Ch, Counting range: 0~16,777,215
		G6F-HD1C	2 CHs, 500kpps, Counting range: -2,147,483,648~-2,147,483,647, Line drive type
		G6F-HO1C	2 CHs, 200kpps, Counting range: -2,147,483,648~-2,147,483,647, Open collector type
Positioning module		G6F-PPxO	X=1, 2, 3: axis, Pulse output, 200kpps, Open collector type
		G6F-PPxD	X=1, 2, 3: axis, Pulse output, 1M, Line drive type
Thermocouple input module	G6F-TC2A	Input: 4 CHs (Thermocouple: K, J, E, T, B, R, S)	GM6-PAFB/PDFB
Comm. module	Fast Enet I/F module (Open type)	G6L-EUTB	10/100BASE-TX, UTP
		G6L-EUFB	100BASE-FX, Fiber optic
	Fast Enet I/F module(Dedicated Master)	G6L-EUTC	10/100BASE-TX, UTP
		G6L-EUFC	100BASE-FX, Fiber optic
	Fast Enet I/F module(Dedicated Slave)	G6L-ERTC	10/100BASE-TX, UTP
		G6L-ERFC	100BASE-FX, Fiber optic
	Fnet I/F module	G6L-FUEA	Fnet master module (Shielded twisted pair cable, 1Mbps)
	Fnet remote I/F module	G6L-RBEA	Fnet remote module (Shielded twisted pair cable, 1Mbps)
	Dnet I/F module	G6L-DUEA	DeviceNet master module (500kbps MAX.)
	Pnet I/F module	G6L-PUEA	Profibus-DP master module (1K)
		G6L-PUEB	Profibus-DP master module (7K)
	Rnet I/F module	G6L-RUEA	Rnet master module
	Cnet I/F module	G6L-CUEB	RS-232C
		G6L-CUEC	RS-422/485
Dummy module	GM6-DMMA	Dummy module for empty I/O slot	

■ GM4

Type	Part Number	Specification	Remarks
CPU	GM4-CPUA	Max. I/O: 2,048 points, Program memory: 128K, Data memory: 52K	
	GM4-CPUB	Max. I/O: 2,048 points, Program memory: 128K, Data memory: 50K	
	GM4-CPUC	Max. I/O: 2,048 points, Program memory: 1M, Data memory: 428K	
Main base	GM4-B04M	4-slot main base board	
	GM4-B06M	6-slot main base board	
	GM4-B08M	8-slot main base board	
	GM4-B12M	12-slot main base board (Slot no. 8 is treated as slot no. 0 of base no. 1)	Not expandable
Main base *	GM4-B4MH	4-slot main base board (High functional)	
(High functional)	GM4-B6MH	6-slot main base board (High functional)	
	GM4-B8MH	8-slot main base board (High functional)	
Expansion base	GM4-B04E	4-slot expansion base board	
	GM4-B06E	6-slot expansion base board	
	GM4-B08E	8-slot expansion base board	
Expansion base *	GM4-B4EH	4-slot Expansion base board (High functional)	
(High functional)	GM4-B6EH	6-slot Expansion base board (High functional)	
	GM4-B8EH	8-slot Expansion base board (High functional)	
Expansion cable	G4C-E041	Length: 0.4m	
	G4C-E121	Length: 1.2m	
	G4C-E301	Length: 3.0m	
Expansion cable *	G4C-E061	Length: 0.6m	
(High functional)	G4C-E601	Length: 6m	
	G4C-E102	Length: 10m	
	G4C-E152	Length: 15m	
Power module	GM4-PA1A	AC 110V input, DC 5V: 4A, DC 24V: 0.7A	
	GM4-PA2A	AC 220V input, DC 5V: 4A, DC 24V: 0.7A	
	GM4-PA2C	AC 220V input, DC 5V: 8A	
	GM4-PD3A	DC 24V input, DC 5V: 4A	
DC input module	G4I-D22A	16 points DC 12/24V input (Current Sink/Source type)	
	G4I-D22B	16 points DC 12/24V input (Current Source type)	
	G4I-D22C	16 points DC 24V input (Current Sink/Source type)	
	G4I-D24A	32 points DC 12/24 input (Current Sink/Source type)	
	G4I-D24B	32 points DC 12/24 input (Current Source type)	
	G4I-D24C	32 points DC 24 input (Current Sink/Source type)	
	G4I-D28A	64 points DC 12/24 input (Current Sink/Source type)	
AC input module	G4I-A12A	16 points AC 110V input	
	G4I-A22A	16 points AC 220V input	
Relay output module	G4Q-RY2A	16 points Relay output (2A)	AC, DC
	G4Q-TR2A	16 points Tr. (NPN) output (0.5A) (Sink type)	
	G4Q-TR2B	16 points Tr. (PNP) output (0.5A) (Source type)	
Transistor output module	G4Q-TR4A	32 points Tr. (NPN) output (0.1A) (Sink type)	DC
	G4Q-TR4B	32 points Tr. (PNP) output (0.1A) (Source type)	
	G4Q-TR8A	64 points Tr. (NPN) output (0.1A) (Sink type)	
Triac output module	G4Q-SS2A	16 points Triac output (1.0A)	AC
	G4Q-SS2B	16 points Triac output (0.6A)	
I/O hybrid module	G4H-DR2A	8 points DC 12/24V input, 8 points relay output	
	G4H-DT2A	8 points DC 12/24V input, 8 points Tr. output	
Special module	A/D module	G4F-AD2A G4F-AD3A	V/I input: 4 CHs (DC -5~5V/-10~10V/DC -20~20mA) V/I input: 8 CHs (DC 1~5V/0~10V/DC 4~20mA)
	D/A module	G4F-DA1A G4F-DA3V G4F-DA3I G4F-DA2V G4F-DA2I	V/I output: 2 CHs (DC -10~10V, DC 4~20mA) V output: 8 CHs (DC -10~10V) I output: 8 CHs (DC 4~20mA) V output: 4 CHs (DC -10~10V) I output: 4 CHs (4~20mA)
	HSC module	G4F-HSCA G6F-HO1C G6F-HD1C	1 CH, 50kHz, Counting range: 0~16,777,215 2 CHs, 200kpps, Counting range: -2,147,483,648~+2,147,483,647, Open collector type 2 CHs, 500kpps, Counting range: -2,147,483,648~+2,147,483,647, Line drive type
	Positioning module	G4F-PPxO G4F-PPxD	X=1, 2, 3: axis, Pulse output, 200kpps, Open Collector Type X=1, 2, 3: axis, Pulse output, 1Mbps, Line Drive Type
	Thermocouple input module	G4F-TC2A	Input: 4 CHs (Thermocouple: K, J, E, T, B, R, S)
	Temperature control module	G4F-TMCA	Temp. control (AI/AO=2/2 CHs) PID 2 loops, 2-point digital output
	RTD input	G4F-RD2A	Input: 4 CHs
	PID control module	G4F-PIDB	Max. 16-loop control (Autotuning), 16-point digital output
	Analog timer module	G4F-AT3A	Input: 8 points
	Interrupt module	G4F-INTA	Input: 8 CHs
	Memory module	GM4-M032	128kbyte (32kstep)

Product list

Programmable Logic Controller

■ GM4

Type	Part Number	Specification	Remarks
Comm. module	Fast Enet	G4L-EUTB	CPU V2.7 ↑
	I/F module (Open type)	G4L-EUFB G4L-EU5B	
	Fast Enet	G4L-EUTC	
	I/F Module (Dedicated Master)	G4L-EUFC G4L-EU5C	
	Fast Enet	G4L-ERTC	
	I/F module (Dedicated Slave)	G4L-ERFC G4L-ER5C	
	Fnet I/F module	G4L-FUEA G4L-FUOA	
	Fnet remote I/F module	G4L-RBEA	
	Dnet I/F module	G4L-DUEA	
	Pnet I/F module	G4L-PUEA G4L-PUEB G4L-PUEC	
	Rnet I/F module	G4L-RUEA	
	Cnet I/F module	G4L-CUEA	
Dummy module	GM4-DMMA	Dummy module for empty I/O slot	
Memory module	G4M-M032	Capacity: 128K (32k steps)	
USB cable	USB-301A	Downloading cable for USB port of GM4-CPUC	GM4-CPUC


* In GM4-CPUC, you are supposed to use high-functional base (main/expansion) and high functional cable when you want to make more than 3-stage expansion.

Dimensions




Programmable Logic Controller

GM7/GM7U



Main



Expansion module



Expansion module (GM7U slim type)




GM7	GM7U	A	B
G7M-D□10A		85	95
G7M-D□20A	G7M-D□20U	135	145
G7M-D□30A	G7M-D□30U	135	145
G7M-D□40A	G7M-D□40U	165	175
G7M-D□60A	G7M-D□60U	215	225

Dimensions


Programmable Logic Controller

GM6


Main



Power



CPU and I/O module




Width of base

(Unit: mm)


	Base board			
A	GM6-B04M	GM6-B06M	GM6-B08M	GM6-B12M
B	230.5	300.5	370.5	510.5
	244	314	384	524

GM4


Base



Power



CPU and I/O module



Width of base

(Unit: mm)


	Base board				Expansion Base		
	GM4-B04M	GM4-B06M	GM4-B08M	GM4-B12M	GM4-B04E	GM4-B06E	GM4-B08E
	GM4-B4MH	GM4-B6MH	GM4-B8MH		GM4-B4EH	GM4-B6EH	GM4-B8EH
A	284	354	424	524	284	354	424
B	297	367	440	540	297	367	437

Cable connection


Programmable Logic Controller

■ Cable connection


Loader cable: K1C-050A




GM6 (A/C), GM7/GM7U loader and built-in Cnet



Rnet cable I (SMART I/O 5pin)




Rnet cable II (SMART I/O 9pin)



Modbus (RS-422)

Modbus master (RS-422) ↔ SMART I/O (9-pin Male)



Leading Innovation, Creating Tomorrow 



- For your safety, please read user's manual thoroughly before operating.
- Contact the nearest authorized service facility for examination, repair, or adjustment.
- Please contact qualified service technician when you need maintenance.
Do not disassemble or repair by yourself!
- Any maintenance and inspection shall be performed by the personnel having expertise concerned.

© 2004.8 LS Industrial Systems Co.,Ltd. All rights reserved.

LS Industrial Systems Co., Ltd.

www.ls-is.com

■ HEAD OFFICE

LS Tower 1026-6, Hogye-dong, Dongan-gu, Anyang-si,
Gyeonggi-do 431-848, Korea

■ Europe	+82-2-2034-4376 / ywsohn@ls-is.com
■ Middle East	+82-2-2034-4901 / bonseongk@ls-is.com
■ South West Asia	+82-2-2034-4645 / sungkyup@ls-is.com
■ South East Asia	+82-2-2034-4707 / ohpark@ls-is.com
■ CIS	+82-2-2034-4913 / jinhkang@ls-is.com
■ America	+82-2-2034-4377 / younsupl@ls-is.com



Specifications in this catalog are subject to change without notice due to
continuous product development and improvement.

■ Global Network

- **LS Industrial Systems (Middle East) FZE** >> **Dubai, U.A.E.**
Address: LOB 19 JAFZA VIEW TOWER Room 205, Jebel Ali Freezone P.O. Box 114216, Dubai, United Arab Emirates
Tel: 971-4-886 5360 Fax: 971-4-886-5361 e-mail: hwym@ls-is.com
- **Dalian LS Industrial Systems Co., Ltd.** >> **Dalian, China**
Address: No.15, Liaohexi 3-Road, Economic and Technical Development zone, Dalian 116600, China
Tel: 86-411-8273-7777 Fax: 86-411-8730-7560 e-mail: lkx@ls-is.com.cn
- **LS Industrial Systems (Wuxi) Co., Ltd.** >> **Wuxi, China**
Address: 102-A , National High & New Tech Industrial Development Area, Wuxi, Jiangsu, 214028, P.R.China
Tel: 86-510-8534-6666 Fax: 86-510-522-4078 e-mail: xuhg@ls-is.com.cn
- **LS-VINA Industrial Systems Co., Ltd.** >> **Hanoi, Vietnam**
Address: Nguyen Khe - Dong Anh - Ha Noi - Viet Nam
Tel: 84-4-882-0222 Fax: 84-4-882-0220 e-mail: srjo@lsisvina.com
- **LS-VINA Industrial Systems Co., Ltd.** >> **Hochiminh , Vietnam**
Address: 41 Nguyen Thi Minh Khai Str. Yoco Bldg 4th Floor, Hochiminh City, Vietnam
Tel: 84-8-3822-7941 Fax: 84-8-3822-7942 e-mail: sbpark@lsisvina.com
- **LS Industrial Systems Tokyo Office** >> **Tokyo, Japan**
Address: 16FL, Higashi-Kan, Akasaka Twin Tower 17-22, 2-chome, Akasaka, Minato-ku Tokyo 107-8470, Japan
Tel: 81-3-3582-9128 Fax: 81-3-3582-2667 e-mail: jschuna@ls-is.com
- **LS Industrial Systems Shanghai Office** >> **Shanghai, China**
Address: Room E-G, 12th Floor Huamin Empire Plaza, No.726, West Yan'an Road Shanghai 200050, P.R. China
Tel: 86-21-5237-9977 (609) Fax: 89-21-5237-7191 e-mail: jinhk@ls-is.com.cn
- **LS Industrial Systems Beijing Office** >> **Beijing, China**
Address: B-Tower 17FL,Beijing Global Trade Center B/D. No.36, BeiSanHuanDong-Lu, DongCheng-District, Beijing 100013, P.R. China
Tel: 86-10-5825-6025,7 Fax: 86-10-5825-6026 e-mail: cuixiaorong@ls-is.com.cn
- **LS Industrial Systems Guangzhou Office** >> **Guangzhou, China**
Address: Room 1403,14F,New Poly Tower,2 Zhongshan Liu Road,Guangzhou, P.R. China
Tel: 86-20-8326-6764 Fax: 86-20-8326-6287 e-mail: linsz@ls-is.com
- **LS Industrial Systems Chengdu Office** >> **Chengdu, China**
Address: Room 1701 17Floor, huanminhanjun international Building, No1 Fuxing Road Chengdu, 610041, P.R. China
Tel: 86-28-8670-3101 Fax: 86-28-8670-3203 e-mail: yangcf@ls-is.com.cn
- **LS Industrial Systems Qingdao Office** >> **Qingdao, China**
Address: 7B40,Haixin Guangchang Sheny Building B, No.9, Shandong Road Qingdao 26600, P.R. China
Tel: 86-532-8501-6568 Fax: 86-532-583-3793 e-mail: irj@ls-is.com.cn